

DISTRIBUTION

SANTA FE

FILE

ALBUQUERQUE

LAND OFFICE

OPERATOR

NEW MEXICO OIL CONSERVATION COMMISSION

Form O-103
Supersedes Old
O-102 and O-103
Effective 1-1-67

Indicate type of notice

Date: _____ From: ☒ X

State: _____

SUNDY NOTICES AND REPORTS ON WELLS

THIS FORM IS TO BE FILLED OUT FOR EACH WELL OR GROUP OF WELLS TO A DIFFERENT RESERVOIR, MADE IN ACCORDANCE WITH THE RULES AND REGULATIONS OF THE COMMISSION.

Unit Agreement Name

Firm or Lessee Name

C. D. Woolworth

Well No.

8

Field or Locality

Jalmat-Yates

Lea

Well ☒ X

Area ☐

Other ☐

Phillips Petroleum Company

Room 806 Phillips Building, Odessa, Texas 79761

4. Location of well

Section M 660 Twp 14 Rng 659 S. 22

Range 24-S Section 36-E

RKB 3348'

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

REPAIRS OR MAINTENANCE WORK

TEMPORARILY ABANDON

WELL OR ALTER CASING

OTHER

PLUG AND ABANDON

CHANGE PLANS

REPAIRS OR MAINTENANCE WORK

CONTINUOUS WELLING LOG

CASING TEST AND CEMENT JOB

OTHER

and add perfs

ALTERING CASING

PLUG AND ABANDONMENT

☒ X

5. Describe in detail all operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 110A.

- 8-3-76: MI Baber WS unit. Pld rods & tbg.
- 8-4-76: Cleaned out frac sand f/3294-3312'. Ram Guns perf 7" csg w/2 jet shots per foot 3292-3302'. Set 2-7/8" tbg at 3272', in Baker "R" pkr, w/stg npl at 3271'.
- 8-5-76: Dowell treated Yates down tbg thru perfs 3292-3302' w/500 gals 15% HCL w/F-75 and A-170, 750 gals super mud acid w/10% U-66 solvent and A-170, 500 gals 3% HCL w/f-75 and A-170, 1000 gals 3% HCL w/A-170 and L-42. Flushed w/24 bbls 2% KCL water w/F-75. Max press 1900#, min pressure-vacuum, final pressure 500#. AIR 2.4 BPM. Released pkr, swbd 6 hrs, 80 BLW and AW. FL 3000'.
- 8-6-76: SI 14 hrs, TP 50#, FL 2500'. Swbd 1 hr, 2 BO, 4 BLW. Pld Baker R pkr. Set 2-7/8" tbg OE at 3215', stg npl at 3185'. Set 2-1/2"x1-3/4"x25' pump at 3185'. MO Baber unit.
- 8-7-76: P/10 hrs, no gauge. Down 14 hrs.
- 8-8-76: P/24 hrs, no gauge.
- 8-9-76: P/24 hrs, no oil, 14 BSW.
- 8-10-76: P/24 hrs, no oil, 21 BSW.
- 8-11-76: P/24 hrs, no oil, 18 BSW.
- 8-12-76: P/24 hrs, 1 BO, 13 BSW.
- 8-13-76: P/24 hrs, 4 BO, 20 BSW.

(over)

BOP: Series 900, 3000# WP, double w/one set pipe rams, one set blind rams, manually operated.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

Signed: W. J. Mueller

TITLE: Engineering Advisor

DATE: 8-23-76

APPROVED BY: _____

TITLE: _____

DATE: _____

CONDITIONS OF APPROVAL, IF ANY:

4062615/5

8-14-76: P/24 hrs, 3 BO, 6 BSW.
 8-15-76: P/24 hrs, 4 BO, 7 BSW.
 8-16-76: P/24 hrs, 3 BO, 6 BSW, gas TSTM.
 8-17-76: P/24 hrs, 3 BO, 6 BSW, gas TSTM, perfs 3236-50'. Restored to production.

REMOVED

917 176

WINDING COIL
 100 IN. DIAMETER
 1/2 IN. DIA. HOLES