

NEW MEXICO STATE LAND OFFICE
OFFICE OF THE STATE GEOLOGIST
SANTA FE, NEW MEXICO

MISCELLANEOUS REPORTS ON WELLS

Submit this report in duplicate to the State Geologist or proper Oil and Gas Inspector within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of water shut-off, result of abandonment of well, and other important operations, even though the work was witnessed by the State Geologist or Oil and Gas Inspector. Reports on minor operations need not be signed and sworn to before a notary public, but such operations should be witnessed by an Oil and Gas inspector if possible.

Indicate nature of report by checking below:

| | |
|--|---|
| REPORT ON BEGINNING DRILLING OPERATIONS | REPORT ON DEEPENING WELL |
| REPORT ON RESULT OF SHOOTING WELL | REPORT ON PULLING OR OTHERWISE ALTERING CASING |
| REPORT ON RESULT OF TEST OF WATER SHUT-OFF | REPORT ON REPAIRING WELL |
| REPORT ON RESULT OF ABANDONMENT OF WELL | Report on Result of sidetracking Halliburton Tester & full hole Packer. |

Bartlesville, Oklahoma October 29, 1934

Place

Date

Mr. E. H. Wells State Geologist,

Santa Fe, N. Mex.

Following is a report on the work done and the results obtained under the heading noted above at the Phillips Petroleum Company C. D. Woolworth Well No. 7 in the SW₄ of Sec 28, T. 24S, R. 54E N. M. P. M., Jal Oil Field, Lea County.

The dates of this work were as follows: October 16 to 23, 1934

Notice of intention to do the work was (10/17/34) submitted on Form SG 106 on October 17, 19 34, and approval of the proposed plan was (10/17/34) obtained. (Cross out incorrect words.)

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

We cut off the remaining 28' of 3" drill pipe leaving 3'11" of 3" drill pipe, Halliburton tester, and full hole packer still in hole. Set whipstock at 3425', top 3435'. Drilled by whipstock to 3464' and milled to 3475' w/ 6 1/2" mill. Put on bit and drilled by whipstock to 3490'. Ran 40 sacks cement and cemented back to 3266'. Drilled out cement to 3200' and cemented 5 1/2" casing at 3472'.

DUPLICATE

Subscribed and sworn to before me this

29 day of October, 19 34

J. R. Carr

Notary Public

My Commission expires 5/16/1938

Remarks:

I hereby swear or affirm that the information given above is true and correct.

Name E. H. Wells

Position Vice President

Representing Phillips Petroleum Company

Company or Operator

Address Bartlesville, Oklahoma.

NOV 2 1934

APPROVED AS NAME

BY F. J. V.

Title

No. C.R.

REPORT OF THE COMMISSIONER OF THE LAND OFFICE

IN RESPONSE TO A RESOLUTION PASSED BY THE SENATE AND ASSEMBLY
JANUARY 18, 1892

ALBANY: J. B. LIPPINCOTT & CO., PRINTERS.

REPORT OF THE COMMISSIONER OF THE LAND OFFICE
IN RESPONSE TO A RESOLUTION PASSED BY THE SENATE AND ASSEMBLY
JANUARY 18, 1892

ALBANY: J. B. LIPPINCOTT & CO., PRINTERS.

ALBANY: J. B. LIPPINCOTT & CO., PRINTERS.

ALBANY: J. B. LIPPINCOTT & CO., PRINTERS.

1892

ALBANY: J. B. LIPPINCOTT & CO., PRINTERS.

ALBANY: J. B. LIPPINCOTT & CO., PRINTERS.

ALBANY: J. B. LIPPINCOTT & CO., PRINTERS.

ALBANY: J. B. LIPPINCOTT & CO., PRINTERS.