

# NEW MEXICO OIL CONSERVATION COMMISSION Santa Fe, New Mexico

## MISCELLANEOUS REPORTS ON WELL

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut-offs, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below:

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL		REPORT ON PULLING OR OTHERWISE ALTERING CASING	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF		REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL	<b>XX</b>		

Hobbs, New Mexico

August 5, 1941

Place

Date

OIL CONSERVATION COMMISSION  
Santa Fe, New Mexico.  
Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the  
Gulf Oil Corp-Gypsy Prodn. Division Vinson-Ramsay State Well No. 2 in the  
Company or Operator Lease

C E/H SE NE of Sec. 12, T. 26S, R. 36E, N. M. P. M.,  
Eaves Field, Lea County

The dates of this work were as follows: August 5, 1941.

Notice of intention to do the work was ~~(was not)~~ submitted on Form C-102 on August 4, 19 41  
and approval of the proposed plan was ~~(was not)~~ obtained. (Cross out incorrect words.)

### DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

Filled hole from total depth (3177') to 2758 with 115 sax cement, mudded to 2600', placed 5 sax cement 2600 to 2587, mudded to 1165 and placed 5 sax cement which filled to 1150', then mudded hole to top and capped with 7 sax cement. Regulation pipe marker cemented in bottom of cellar and extending 4' above ground level.

Pipe left in hole: 1 jt - 13" soil pipe, cemented to top with 50 sax.

1172' - 8 5/8" casing, cemented with 550 sax 4% Aquagel cement,  
cement circulated in the cellar.

Well abandoned as a dry hole.

Witnessed by G. C. Cummings. Gulf Oil Corporation Dist. Superintendent  
Name Company Title

Subscribed and sworn to before me this 5th  
day of August, 19 41

J. W. Eames

Notary Public

I hereby swear or affirm that the information given above is true and correct.

Name G. C. Cummings

Position District Superintendent

Representing Gulf Oil Corp-Gypsy Prodn. Div.  
Company or Operator

Address Hobbs, New Mexico.

My Commission expires February 25, 1942.

Remarks:

Roy Yarbrough  
Name

OIL & GAS INSPECTOR

Title