

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

MISCELLANEOUS NOTICES

Submit this notice in triplicate to the Oil Conservation Commission or its proper agent before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of notice by checking below:

NOTICE OF INTENTION TO TEST CASING SHUT-OFF	NOTICE OF INTENTION TO SHOOT OR CHEMICALLY TREAT WELL
NOTICE OF INTENTION TO CHANGE PLANS	NOTICE OF INTENTION TO PULL OR OTHERWISE ALTER CASING
NOTICE OF INTENTION TO REPAIR WELL	
NOTICE OF INTENTION TO DEEPEN WELL	NOTICE OF INTENTION TO PLUG WELL XX

Hobbs, New Mexico

Place

August 4, 1941

Date

OIL CONSERVATION COMMISSION,
Santa Fe, New Mexico.

Gentlemen:

Following is a notice of intention to do certain work as described below at the Gulf Oil Corporation

Gypsy Prodn. Division Vinson-Ramsey State Well No. 2 in C E/H SE NE
Company or Operator Lease

of Sec. 12, T. 26S, R. 36E, N. M. P. M., Eaves Field,
Lea County.

FULL DETAILS OF PROPOSED PLAN OF WORK

FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS OF THE COMMISSION

Elevation: 2953'. Total Depth 3177'. Formation Record: Top Anhydrite 1080', Base Salt 2590', Top Yates 2780', Top Reef Dolomite 2970. 8 5/8" casing set at 1172' and cemented to top. Halliburton Drill-Stem tests as follows: 2760-2980, showed 150' rotary mud, no oil, gas; 2970-3025, showed estimated 20 bbls sulphur water per hour & very little gas; 3032-3080, showed 2280' of sulphur water with 112,000 cu.ft. gas daily; 3048-3177, estimated 15 bbls water per hour, no oil, gas 120,000 cu.ft. daily. In the absence of any oil, and with such a small amount of gas, propose to plug and abandon in following manner: Cement from T.D. to 2760', mud to 2590' (Base salt), place 5' cement plug at that point, mud to bottom of 8 5/8" casing and place 5' cement plug, mud to top of hole and cap with cement, placing the regulation 4" pipe marker.

AUG 4 1941

Approved _____, 19____
except as follows:

Gulf Oil Corp-Gypsy Prodn. Division

Company or Operator

By

Position District Superintendent

Send communications regarding well to

Name C. C. CummingsAddress Hobbs, New Mexico

OIL CONSERVATION COMMISSION,

By

Title

OIL & GAS INSPECTION