

SANTA FE		
FILE		
U.S.G.S.		
LAND OFFICE		
OPERATOR		

NEW MEXICO OIL CONSERVATION COMMISSION

L.P. RESOURCES DIV.
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease

State ☒Fee ☐

5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)OIL
WELL ☐GAS
WELL ☐

OTHER- Re-entry

Name of Operator

Maralo, Inc.

Address of Operator

P. O. Box 832, Midland, Texas 79702

Location of Well

UNIT LETTER M 660 FEET FROM THE South LINE AND 660 FEET FROM
THE West LINE, SECTION 16 TOWNSHIP 26-S RANGE 36-E NMPM.

7. Unit Agreement Name

8. Farm or Lease Name

Maralo "16" State

9. Well No.

6

10. Field and Pool, or Wildcat

Sioux Yates

15. Elevation (Show whether DF, RT, CR, etc.)

2946' GL

12. County

Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐TEMPORARILY ABANDON ☐FILL OR ALTER CASING ☐OTHER ☐PLUG AND ABANDON ☐CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☒COMMENCE DRILLING OPNS. ☐CASING TEST AND CEMENT JOB ☐OTHER ☐ALTERING CASING ☐PLUG AND ABANDONMENT ☒

Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work.) SEE RULE 1103.

Commenced operations 2-29-80 - Dug out cellar and removed 4" marker. Welded on 13 3/8" csg. Installed cellar. Installed BOP. Drld. 5' cement plug to open casing. Tagged plug @ 188'. Washed to 278' open hole to 600'. Drld. Washed to 679'. Checked for leak is csg. - 15' from surface. Squeezed w/50 sx Class C 50% Calseal.WOC 3 hrs. Drod. out cement. Washed & circ. hold clean. Ran 5 stands to bottom 963'. Washed and cleaned to top of 9 5/8" csg. to 1004'. Circ'd hole clean. Tagged 9 5/8" csg. @ 1006'. POH. Lay down 6 - 4 3/4" DC, subs and 11" bit. WIH w/2 7/8" 8 rd upset N-80 tbg. to bottom of 13 3/8" csg. Rigged down reverse unit. SDON Ran tbg. open ended to 1005'. Sptd. 65 sx Class C cement 2% CaCl2. Lay down 10 jts. 2 7/8" tbg. to 686'. Spotted 60 sx Class C cement 2% CaCl2. TOC @ 636'. Spotted 50 sx Class C cement 2% CaCl2 @ 636' 75' plug to 561'. Lay down all tbg. Plug top of 13 3/8" casing. 10' cement. Installed dry hole marker. Well plugged & abandoned 3-16-80
Pits have been filled and location levelled and cleared of junk.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

BY Brenda CoffmanTITLE Production ClerkDATE 6-5-81BY Ronald CastleberryTITLE DATE

CONDITIONS OF APPROVAL, IF ANY: