

[illegible]

## NEW MEXICO STATE LAND OFFICE

**SANTA FE, NEW MEXICO**

## DEPARTMENT OF THE STATE GEOLOGIST

## WELL RECORD

Mail to State Geologist, Santa Fe, New Mexico, not more than ten days after completion of well. Indicate questionable data by following it with (?). Submit in duplicate.

Company Gypsy Oil Company Address Tulsa, Oklahoma.  
Send correspondence to Gypsy Oil Company Address Hobbs, New Mexico.  
Vinson-Ramsay 'A' Well No. 1 in SE/4 of Sec. 12, T. 36S  
R. 36E, N. M. P. M., Jal Oil Field Lea County.  
If State land the oil and gas lease is No. 15822 Assignment No. \_\_\_\_\_  
If patented land the owner is \_\_\_\_\_, Address \_\_\_\_\_  
The lessee is Gypsy Oil Company, Address Tulsa, Oklahoma  
If not state or patented land, give status \_\_\_\_\_  
Drilling commenced June 2nd 19 35 Drilling was completed August 18th 19 35  
Name of Drilling contractor Laffland Bros., Address Tulsa, Oklahoma.  
Elevation above sea level at top of casing 2956' feet.  
The information given is to be kept confidential until Not Confidential 19 \_\_\_\_\_

## OIL SANDS OR ZONES

No. 1, from **3140'** to **3180'** No. 4, from \_\_\_\_\_ to \_\_\_\_\_  
 No. 2, from \_\_\_\_\_ to \_\_\_\_\_ No. 5, from \_\_\_\_\_ to \_\_\_\_\_  
 No. 3, from \_\_\_\_\_ to \_\_\_\_\_ No. 6, from \_\_\_\_\_ to \_\_\_\_\_

## IMPORTANT WATER SANDS

No. 1, from \_\_\_\_\_ to \_\_\_\_\_      No. 3, from \_\_\_\_\_ to \_\_\_\_\_  
No. 2, from \_\_\_\_\_ to \_\_\_\_\_      No. 4, from \_\_\_\_\_ to \_\_\_\_\_

## CASING RECORD

[illegible]

## MUDDING AND CEMENTING RECORD

SIZE	WHERE SET	NO. SACKS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED
13"	317'	250	Halliburton		
9-5/8"	2066'	800	Halliburton		
7"	2897'	300	Halliburton		

## PLUGS AND ADAPTERS

Heaving plug—Material \_\_\_\_\_ Length \_\_\_\_\_ Depth Set \_\_\_\_\_  
Adapters—Material \_\_\_\_\_ Size \_\_\_\_\_

## SHOOTING RECORD

SIZE	SHELL USED	EXPLOSIVE USED	QUANTITY	DATED	DEPTH SHOT	DEPTH CLEANED OUT

## TOOLS USED

Rotary tools were used from 0 feet to 3228' feet, and from \_\_\_\_\_ feet to \_\_\_\_\_ feet

Cable tools were used from \_\_\_\_\_ feet to \_\_\_\_\_ feet, and from \_\_\_\_\_ feet to \_\_\_\_\_ feet

## PRODUCTION

Put to producing Sept 10th, 1935

The production of the first 24 hours was 165 barrels of fluid of which 92% % was oil; \_\_\_\_\_ % emulsion; 8 % water; and \_\_\_\_\_ % sediment. Gravity, Be 3118

If gas well, cu. ft. per 24 hours \_\_\_\_\_ Gallons gasoline per 1,000 cu. ft. of gas \_\_\_\_\_

Rock pressure, lbs. per sq. in. \_\_\_\_\_

## EMPLOYEES

<u>Carl Simpson</u>	Driller	<u>Gus Everett</u>	Driller
<u>Jack Reynolds</u>	Driller	<u>C.C. Fielden.</u>	Driller

FORMATION RECORD ON OTHER SIDE

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

Subscribed and sworn to before me this 3  
day of October, 1935  
John L. Emerson  
JUSTICE OF THE PEACE, SEBASTIAN, TENN.

Name P. J. Cummings  
Position \_\_\_\_\_

## FORMATION RECORD

FROM	TO	THICKNESS IN FEET	FORMATION
0	188		Sand and Red Rock
188	308		Red Rock
308	555		Red Rock and Shells
555	671		Red Rock and Shells and Sand
671	759		Shale and shells
759	856		Red Rock and Shells
856	1102		Red Rock and Shale
1102	1174		Shale and Anhydrite
1174	1315		Anhydrite and salt
1315	1438		Salt and Anhydrite
1438	1580		Anhydrite and Salt
1580	1596		Salt and Shells
1596	2082		Anhydrite and Salt.
2082			
Steel Drill Pipe Meas.	2095		
2095	2102		Anhydrite
2102	2410		Salt and Anhydrite
2410	2685		Salt
2685	2685		Line
2685	2701		Broken Line,
2701	2895		Line
2895	3049		Line
3049	3072		Line
3072	3097		Line
3097	3120		Line
3120	3131		Line
3131	3132		Line
3132	3144		Line
3144	3155		Line
3155	3196		Line
3196	3228		Line and sand
3228			Plugged back to 3180'