

Form 3160-5
(July 1989)
(Formerly 9-331)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

CONTACT RECEIVING
OFFICE FOR NUMBER
OF COPIES REQUIRED
(Other instructions on reverse
side)

BLM Roswell District
Modified Form No.
NM060-3160-4

5. LEASE DESIGNATION AND SERIAL NO.

LC-056927-A

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

EL PASO NATURAL GAS

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

SCARBOROUGH Y-5 R

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

13, T-26-S, R-36-E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

2950' DF

12. COUNTY OR PARISH

LEA

13. STATE

N.M.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

16.

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

☐
☐
☐
☐
☐

PULL OR ALTER CASING

☐
☐
☐
☐
☐

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON*

REPAIR WELL

CHANGE PLANS

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

☐
☐
☐

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

☐
☐
☒
☐

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

AMBETT OIL COMPANY WAS THE OPERATOR OF THIS WELL. THE BLM REPEATLY REQUESTED AMBETT OIL CO TO PLUG AND ABANDON THIS WELL WITH NO RESPONSE. AMBETT OIL CO. FAILED TO HONOR PLUGGING OBLIGATION AND IT REVERTED BACK TO MERIDIAN WHO WAS THE TITLE HOLDER OF RECORD.

2-23-89 RIH W/3-3/4" BIT, 4-1/2" CSG SCRAPER & 2-3/8" WORKSTRING TO 3179'. SET CIBP @ 3156', SPOT 35' CEMENT ON TOP OF CIBP. DISPLACED CSG W/10# MUD LADEN BRINE WATER, TEST CSG TO 500 PSI. PERF'D 4 SQUEEZE HOLES @ 2650'. ESTABLISHED RATE 3 BPM @ 800 PSI. SET CMT RETAINER @ 2548', COULD NOT PUMP UNDER RETAINER. SPOT 25 SXS CMT ON TOP OF RETAINER PER BLM. PERF'D 4 SQUEEZE HOLES @ 1150'. EST RATE 2-1/2 BPM @ 650 PSI. SET CMT RETAINER @ 1050', SQUEEZE W/50 SXS CMT, STING OUT OF RET, CAP W/ 10 SXS CMT. PERF'D 4 SQUEEZE @ 360'. SET PKR AT 200', EST RATE 3.5 BPM @ 150 PSI, CIRC'D TO SURF. PUMP'D 50 SXS CMT, WOC. TIH W/TBG OPEN ENDED TO 93', SPOT 10 SXS CMT TO SURF. CUT OFF WELL HEAD. INSTALL DRY HOLE MARKER. RESTORED LOCATION. WELL P&A'D 2-23-89.

WELL WAS P&A'D PER BLM INSTRUCTION ON LOCATION.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

PROD. ASST.

DATE

3-11-92

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

3-17-92

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side