

## NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

HOBBS OFFICE OCC

## MISCELLANEOUS NOTICES

Submit this notice in TRIPLICATE to the District Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL		NOTICE OF INTENTION TO DRILL DEEPER	
NOTICE OF INTENTION TO PLUG WELL	X	NOTICE OF INTENTION TO PLUG BACK		NOTICE OF INTENTION TO SET LINER	
NOTICE OF INTENTION TO SQUEEZE		NOTICE OF INTENTION TO ACIDIZE		NOTICE OF INTENTION TO SHOOT (Nitro)	
NOTICE OF INTENTION TO GUN PERFORATE		NOTICE OF INTENTION (OTHER)		NOTICE OF INTENTION (OTHER)	

OIL CONSERVATION COMMISSION  
SANTA FE, NEW MEXICOHobbs, New Mexico  
(Place)January 11, 1960  
(Date)

Gentlemen:

Following is a Notice of Intention to do certain work as described below at the

Cities Service Oil Company, Sand Hills Unit, Well No. 6 in P  
(Company or Operator) Lease (Unit)  
SE 1/4, SE 1/4 of Sec. 20, T. 36-N, R. 30-W, NMPM, Wildcat Pool  
(40-acre Subdivision)  
Lea County.

FULL DETAILS OF PROPOSED PLAN OF WORK  
(FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

This well was drilled to 1257' in Sand and Shale. Run 2 1/2" of 13-3/8" OD 484 SR 8-40 SS casing set at 253'. Run 1081.57' of 8-5/8" OD 364 SR 8-40 casing set at 1094.39'. Cement was drilled out to 967' and drilled out drill deeper due to the fact that the 8-5/8" casing was parted. The 8-5/8" casing was shot off at 1094' and parted. It is now proposed to plug to abandon this well by loading the hole with mud (heavy fluid); spotting 100 sacks of cement on bottom, if possible; spot 20 sacks of cement at the point where 8-5/8" casing is shot off; spot 50 sacks of cement at the base of the 13-3/8" casing; spot 10 sacks of cement at the top of the 13-3/8" casing with 4" marker located 10' above the surface. The pits will be filled and location will be cleared of all debris.

Approved....., 19.....  
Except as follows:

Approved  
OIL CONSERVATION COMMISSION

By.....  
Title.....

Cities Service Oil Company, as Agent of Sinclair  
Oil & Gas Company - Operator of Sand Hills Unit  
Company or Operator

By.....

Position.....  
Send Communications regarding well to:

Name.....

Address..... Hobbs, New Mexico