

**APPROVED**  
\*Subject to: Casing on the 5 1/2" casing must be returned into the  
8 5/8" casing 3,000'.  
Budget Bureau No. 42-R368.4.  
Approval expires 12-31-60.


NOV 14 1961

(SUBMIT IN TRIPLICATE)

Land Office SANDS, P.E., N.M.

Lease No. LC-032452(b)

Unit \_\_\_\_\_



E. W. STANDLEY  
DISTRICT ENGINEER

**UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY**

**SUNDRY NOTICES AND REPORTS ON WELLS**

|   |                                     |   |  |
|---|-------------------------------------|---|--|
| NOTICE OF INTENTION TO DRILL.....                   | <input checked="" type="checkbox"/> | SUBSEQUENT REPORT OF WATER SHUT-OFF.....        |  |
| NOTICE OF INTENTION TO CHANGE PLANS.....            |                                     | SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING..... |  |
| NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....     |                                     | SUBSEQUENT REPORT OF ALTERING CASING.....       |  |
| NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL..... |                                     | SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR..... |  |
| NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....        |                                     | SUBSEQUENT REPORT OF ABANDONMENT.....           |  |
| NOTICE OF INTENTION TO PULL OR ALTER CASING.....    |                                     | SUPPLEMENTARY WELL HISTORY.....                 |  |
| NOTICE OF INTENTION TO ABANDON WELL.....            |                                     |   |  |

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

November 13, 1961

Well No. 1 is located 660 ft. from N line and 660 ft. from E line of sec. 1

W/2, SW/4 Sec. 1 23-S 37-E  
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)  
Wilcox Lee N.M. (P.M.)  
(Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is \_\_\_\_\_ ft. to be submitted at a

**DETAILS OF WORK** later date.

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Ellenburger test, 9000'. 13-3/8" surface casing @ 350'. Circulated.  
8-5/8" intermediate casing @ 9000'.  
Cement circulated.  
3 1/2" oil string at 9000'. Cemented with  
sufficient volume to cover all producing  
intervals.

Drill Stem Tests 5800'. Glorietta. (1)  
5800-6800'. Clearfork & Tubb (2) & (3)  
6800'. Abc (4)  
7300'. Penn. (5)  
7600'. Devonian (6)  
Total depth. Ellenburger (7)

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Blair & Price, Agent for Samedan Oil Corporation

Address 122 North "N" St.

Midland, Texas

By W. G. Griffith

Title Agent, Blair & Price.