


N.

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

WELL RECORD



Mail to Oil Conservation Commission, Santa Fe, New Mexico, or its proper agent not more than twenty days after completion of well. Follow instructions in the Rules and Regulations of the Commission. Indicate questionable data by following it with (?). SUBMIT IN TRIPLICATE.

DUPLICATE

AREA 640 ACRES
LOCATE WELL CORRECTLY

INTERCOAST PETROLEUM CORP.'N.-J.C. CLOWER

EUNICE, N.M.

Company or Operator

Address

State

Well No. 1

in SW SW SW

of Sec. 2

T. 23

Lease

R. 37

N. M. P. M.

Skelly Area

Field,

Lea

County.

Well is 2310 feet south of the North line and 4950 feet west of the East line of S 2 T 23 R 37

If State land the oil and gas lease is No. B-85 Assignment No.

If patented land the owner is Address

If Government land the permittee is Address

The Lessee is Intercoast Petroleum Corpn-J.C. Clower Address Eunice, N.M.

Drilling commenced March 5, 1938 Drilling was completed April 16, 1938

Name of drilling contractor J.C. Clower Address Eunice, N.M.

Elevation above sea level at top of casing 3297 feet.

The information given is to be kept confidential until 19

OIL SANDS OR ZONES

No. 1, from to No. 4, from to

No. 2, from to No. 5, from to

No. 3, from to No. 6, from to

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from 765 to 780 feet.

No. 2, from to feet.

No. 3, from to feet.

No. 4, from to feet.

CASING RECORD

SIZE	WEIGHT PER FOOT	THREADS PER INCH	MAKE	AMOUNT	KIND OF SHOE	CUT & FILLED FROM	PERFORATED FROM TO	PURPOSE
10 3/4	40	8		140				Surface
8 5/8	11.29.35	8		1145				Salt string
7 OD	22	10		3392				oil string

MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED
18	10 3/4	140	100	Pump & Plug	10 lb	Hole Full
10	8 5/8	1145	100	Pump & Plug	10 lb.	Hole Full
8 in	7 OD	3392	150	Pump & Plug	10 lb.	Hole Full

PLUGS AND ADAPTERS

Heaving plug—Material Length Depth Set

Adapters—Material Size

RECORD OF SHOOTING OR CHEMICAL TREATMENT

SIZE	SHELL USED	EXPLOSIVE OR CHEMICAL USED	QUANTITY	DATE	DEPTH SHOT OR TREATED	DEPTH CLEANED OUT

Results of shooting or chemical treatment

RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto.

TOOLS USED

Rotary tools were used from 0 feet to 3658 feet, and from feet to feet

Cable tools were used from 0 feet to 3658 feet, and from feet to feet

PRODUCTION

Put to producing 19

The production of the first 24 hours was 0 barrels of fluid of which % was oil; %

emulsion; % water; and % sediment. Gravity, Be

If gas well, cu. ft. per 24 hours Gallons gasoline per 1,000 cu. ft. of gas

Rock pressure, lbs. per sq. in.

EMPLOYEES

Fred Whitaker Driller Grady Roberts Driller

F.H. French Driller Driller

FORMATION RECORD ON OTHER SIDE

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

Subscribed and sworn to before me this 18

day of April, 1938

Notary Public

My Commission expires Dec 10, 1940

Eunice, N.M. April 18, 1938.

Name J.C. Clower

Position Part Owner

Representing Intercoast Pet. Corpn. & J.C. Clower Company or Operator

Address Sr. #380, Eunice, N.M.

FORMATION RECORD

FROM	TO	THICKNESS IN FEET	FORMATION
0	10	10	Cellar
10	15	5	Rock
15	50	35	Clay
50	90	40	Sand
90	97	7	Shale
97	100	3	Gravel
100	240	140	Shale
240	253	13	Sand
253	715	462	Shale
715	722	7	Sand
722	755	43	Sandy Shale
755	780	15	Water Sand
780	1183	403	Shale
1183	1272	89	Anhydrite
1272	2892	1620	Salt, Shale, Anhydrite & Potash
2892	3029	137	Lime & Anhydrite
3029	3055	26	Brown Lime & Anhydrite
3055	3193	134	Lime & Anhydrite
3193	3198	5	Shale
3198	3245	47	Lime
3245	3265	20	Lime & Shale
3265	3275	10	Lime
3275	3355	90	Lime & Anhydrite
3355	3441	6	Lime
3441	3450	9	Lime & Shale
3450	3500	50	Lime
3500	3504	4	Blue Shale
3504	3549	45	Lime
3549	3558	9	Sandy Lime
3558	3571	13	Sandy Lime & Shale
3571	3580	9	Sand
3580	3588	8	Lime
3588	3598	10	Sandy Lime
3598	3612	14	Sand & Shale
3612	3657	45	Lime
3657	3658	1	Sulphur Water.