

FORMATION RECORD

FROM	TO	THICKNESS IN FEET	FORMATION
Top	84	84	Sand
84	243	159	Sand and shale
243	386	143	Red Rock, Sand & Shale
386	488	102	Sand & Red Bed
488	722	234	Red Rock & Red Bed
722	965	243	Red Rock & Shale
965	1105	140	Red Rock
1105	1284	179	Anhydrite
1284	1472	188	Red Rock & Salt
1472	1768	296	Red Rock, Salt & Anhydrite
1768	1866	98	Salt & Anhydrite
1866	1965	99	Anhydrite, Salt & Potash
1965	2107	42	Salt & Potash
2107	2450	343	Salt
2450	2660	210	Anhydrite
2660	2698	38	Anhydrite & Gypsum
2698	2756	58	Anhydrite & Lime
2756	2811	55	Lime
2811	2860	49	Anhydrite & Lime
2860	3320	460	Lime
3320	3330	10	Lime
3320	3343	13	Med. Soft Brown Lime
3343	3380	37	Brown Lime
3380	3405	25	Broken Lime
3405	3424	19	Gray Lime
3424	3440	16	White Lime
3440	3478	38	Gray Lime
3478	3499	21	Gray Sandy Lime
3499	3509	10	Med. Soft Gray Lime
3509	3520	11	Soft Sandy Gray Lime
3520	3524	4	Hard Gray Lime
3524	3545	21	Soft Oil Sand
3545	3550	5	Hard Lime
3550	3558	8	White Lime (Hard)
3558	3566	8	Gray Lime
3566	3582	16	Med. Soft Sand
3582	3587	5	Broken Lime
3587	3588	1	Hard Gray Lime
3588	3600	12	Hard White Lime
3600	3610	10	Med. Soft Gray Lime
3610	3625	15	Light Gray Lime
3630' TD - SLM correction from 3625' to 3630'.			