

OPERATOR LEASE/WELL NO.	LOCATION	DATE DRILLED	TOTAL DEPTH	CASING	TYPE	COMPLETION RECORD
<u>Texaco Producing Inc.</u>						
Ellen Sims No. 6	Unit J, 1980' FSL & 1830' FEL, 3-T20S- R31E		6615'	13-3/8" @ 153' w/150 sxs, cmt circ.; 8-5/8" @ 2790' w/800 sxs, calc. TOC @ 1217'; 5-1/2" @ 6390' w/300 sxs, calc. TOC @ 4795'	Oil, P&A	O.H. 6390'-6615'; 12-22-48 500 gal mud acid; 12-23-48 2000 gal 15% HCL; P&A, September, 1950, cut 5-1/2" csg. @ 4290' & pulled, 20 sx plug @ 6615'-6550', 20 sx plug @ 4402'-4340', 45 sx plug @ 3825'- 3678', 75 sx plug @ 3680'-3400', 10 sx plug @ 2790'-2760', 20 sx between 13-3/8" & 8-5/8", 20 sx plug @ surface in 8-5/8"; c/o & P&A December, 1974, c/o to 2845', 50 sx plug @ 2573'-2817', perf 8-5/8" @ 1100' w/2 holes, drill out cmt. plug 2573'- 2817'; c/o to 3317', 200 sx plug @ 2550'- 3315', sqz. 8-5/8" perfs w/200 sxs, 20 sx cmt. plug @ 0'-64', all other intervals filled w/10.2#/gal mud.
Sims "D" No. 2	Unit F, 2310' FNL & 3300' FEL, 3-T23S- R37E		6620'	13-3/8" @ 159' w/150 sxs, cmt circ.; 8-5/8" @ 2790' w/1000 sxs, cmt circ.; 5-1/2" @ 6440' w/300 sxs, calc TOC @ 5060'	Oil, P&A	O.H. 6440'-6620'; 11-10-48 700 gal mud acid @ 6455'-6620'; 11-15-48 3000 gal 15% HCL @ 6455'-6620'; 11-17-48 7000 gal 15% HCL @ 6455'-6620'; P&A May, 1949, cut 5-1/2" csg. @ 4400' & pulled, 25 sx plug @ 6620'-6396', 15 sx plug @ 4800'-4674', 54 sx plug @ 3600'-3400', 10 sx plug @ 2750'- 2720', cmt. plug @ 0'-10'; c/o & P&A December, 1974; c/o to 3460', sqz. O.H. @ 2727'-3460' w/400 sxs, sqz. 8-5/8" csg. leaks @ 2438'-2470' w/150 sxs, perf 8-5/8" csg. w/2 holes @ 1100', sqz. 8-5/8" csg. perfs w/200 sxs, 30 sx plug @ 0'-100', all other intervals filled w/10.2#/gal mud.

JUL 18 1965

RECEIVED