

OIL CONSERVATION COMMISS

Miscellaneous Reports on

Submit this report in triplicate to the Oil Conservation Commission

Indicate natu	re of ren	ort by checking belo	ports on minor operations ules and Regulations of th	e Commission.
·		of onorwing pero	····	
REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON F	EPAIRING WELL	
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL		REPORT ON P	ULLING OR OTHERWIS	E
REPORT ON RESULT OF TEST OF CASING SHUT-OFF	XX	REPORT ON I	DEEPENING WELL	
EPORT ON RESULT OF PLUGGING OF WELL				
	Jur	ne 28, 1950	Hobbs.	New Mexico
IL CONSERVATION COMMISSION,		Date	Plac	********
NTA FE, NEW MEXICO. Intlemen: Intlowing is a report on the work done and the results.	ılts obtai	ned under the headin	g noted above at the	
SCILL OUR SILV		King Film	·· · · · · · · · · · · · · · · · ·	
Company or Operator SW/a WW/a		Lease	weii No	in the
of Sec. 0	, '	т. 238	, R 371	NMPM
Field				
le dates of this work were as follows:	. 1950			
otice of intention to do the work was (was set) s	ubmitted	on Flores C 100	June 26	F
. ,				
d approval of the proposed plan was (XXXXXX	oktoined	(Cream C-102 on		19
d approval of the proposed plan was (ot tained.	(Cross out incorrect	words.)	19
DETAILED ACCOUNT OF	obtained. WORK	(Cross out incorrect DONE AND RESUL	words.) TS OBTAINED	-A -A 30500
DETAILED ACCOUNT OF rilled to total depth of 1350 in a nd comented with 600 sacks coment. urface. Waited 36 hours for coment lug and tested casing shut-off. Shu	ottained. WORK nhydri Hallib to set	Cross out incorrect DONE AND RESUL te. Ran string ourton process and on June 27	words.) TS OBTAINED 9-5/8"00 casing so used and coment cir 7, 1950, at 12:30 I drilling shead.	ot at 1350
DETAILED ACCOUNT OF rilled to total depth of 1350° in a nd cemented with 600 sacks cement. urface. Waited 36 hours for cement lug and tested casing shut-off. Shu	obtained. WORK nhydri Hallib to set t-off	Cross out incorrect DONE AND RESUL te. Ran string out on process and on June 27 tested OK. Now Ed. W. Canned Company I hereby swear or a	words.) TS OBTAINED 9-5/8"00 casing so used and coment cir 7, 1950, at 12:30 I drilling shead.	et at 1350° reulated to P.M. drille
DETAILED ACCOUNT OF rilled to total depth of 1350 in a nd cemented with 600 sacks cement. urface. Waited 36 hours for cement lug and tested casing shut-off. Shu itnessed by Ri. W. Cannedy.	obtained. WORK nhydri Hallib to set t-off	(Cross out incorrect DONE AND RESUL te. Ran string out on process a and on June 27 tested OK. Now Ed. W. Canned Company	words.) TS OBTAINED 9-5/8"OD casing so used and cement cir., 1950, at 12:30 l drilling shead.	roulated to P.M. drille Tool Bu
DETAILED ACCOUNT OF Tilled to total depth of 1350 in a nd cemented with 600 sacks cement. urface. Waited 36 hours for cement lug and tested casing shut-off. Shu itnessed by Rie W. Cannedy Name	obtained. WORK nhydri Hallib to set t-off	Cross out incorrect DONE AND RESUL te. Ran string out on process in and on June 27 tested OK. Now Ed. W. Canned Company I hereby swear or a is true and correct. Name	words.) 75 OBTAINED 9-5/8"00 casing action and sement circles, 1950, at 12:30 I drilling ahead.	roulated to P.M. drille Tool Bu
DETAILED ACCOUNT OF TILLED ACC	obtained. WORK nhydri Hallib to set t-off	Cross out incorrect DONE AND RESUL te. Ran string out on process in and on June 27 tested OK. Now Rd. W. Canned Company I hereby swear or a is true and correct. Name Position	words.) TS OBTAINED 9-5/8"OD casing so used and cement cir., 1950, at 12:30 I drilling shead.	roulated to P.M. drille Tool Bu

Title