| FFILE DR | ALE MERICA GALLER MERICAN | | Fielder offic Filles of the Filles of the Filles Filles A Fielder Fielder No. Filles A Fielder Fielder No. |
|--|--|--|---|
| SAS (| Water Injectio | on | Skelly Penrose "A" Unit |
| Skelly Oil Company | | | Skelly Penrose "A" Unit |
| P. O. Box 1351, Midlan | d, Texas 79701 | | 48 |
| East | 1980 North 9 23S | 660 37E | Langlie-Mattix |
| Check | Appropriate the local state of the second stat | 99' DF | |
| | e de la companya de l La companya de la comp | | |
| национала Каральрон — — — — — — — — — — — — — — — — — — — | an Parisan an Arian An Parisan an Arian An | Set 5" OD ca and treat Pe | sing liner, perforate, X |
| Perforated 7" OD c Spotted 250 gals. Perforated 7" OD c at 2596' and 2600' Cleaned out 3550-3 Set 16 jts. (529') Cemented 5" OD cas gelsonite per sack Drilled cement in Perforated 5" OD 1 3558', 3588-3592', Treated perfs. 349 flushed with 45 bb Set 110 jts. (3314) | rig. Pulled injection tub asing at 2600' with two 0. 15% acid across perfs. 260 asing at 2596' with two 0. with 3000# pressure. 709' TD. 5" OD casing liner 3180-3 ding liner with 200 sacks Of and 100 sacks Class "C" c 5" OD casing liner 3165-36 iner at 3494-3498', 3508-3 3604-3607', 3611-3614', 3 94-3634' with 6000 gals. 15 ls. water. ') 2-3/8" OD cement lined ection status, injecting F | 49" diameter holes 49" diameter holes 49" diameter holes 3709'. Class "C" cement, 0 cement with 2% CaCl 555' PBTD. 3514', 3524-3528', 3629-3634', total o 5% NE acid with 280 tubing in injectio | a. Unable to breakdown perfs. b.5% CFR2, 3# salt, 5# c. WOC 63 hours. 3533-3537', 3540-3543', 3554- bf 80 shots. b0# rock salt in 4 stages, bn packer at 3321'. |
| | | ad Clerk | 3-31-75 |