FORM C-105								
N.	• • • • •		NEW ME	XICO O	IL CONSERVA	ATION COMMISS	SION	
					Santa Fe, New	Mexico		
						MERCE		
	·					MA: 26	3 1938	
• •	······				WELL BECOM	1111		
					WELL RECOR			
	0				<u></u>	HOBBS	DFFICE	
		м	til to Oil Co	ngongution C	american Street T			
		ag	gent not more	than twenty	days after completi	Fe, New Mexico, or its on of well. Follow inst	ructions	
AREA 640 AC	CRES				UBMIT IN TRIPLI			
LOCATE WELL CO	RRECTLY					DUPL	ICATE	
Gulf 011 C	orporatio	on			Tulsa	Oklahoma		
(Company or Ope	rator				Address		
Nick Alley	<u> </u>	Vell No	L	in N L	of Sec.	0, т	238	
R. 37E	N. M. P. M.,	Ske	11 y	Field, _	Le	8.	County.	
Well is 660 fee	et south of the	North lir	ne and 66	0feet	west of the East 1	ine of NE S	E	
If State land the oil a	und gas lease i	s No		Assignn	nent No			
If patented land the o	waer is				, Address			
If Government land	the permitt e e	is	·		, Address			
The Lessee is	Gulf O	<u>11 Oor</u>	poratio	n	, Address	Tulsa, Okl	ahoma	
Drilling commenced_	3-12-		19 3	8. Drillin	g was completed	4-28-	<u>19</u> 38	
Name of drilling con			-				-	
Elevation above sea l						•		
The information give								
Penrose Sand								
						to		
No. 2, from				No. 4, fromtoto				
No. 3, from								
, , , , , , , , , , , , , , , , , , ,			MPORTANT					
Include data on rate								
No. 1, from Ro	-					et		
No. 2, from								
No. 3, from								
No. 4, from			.to		fee	et		
			CASIN	G RECORI	D			
WEIGHT	THREADS			KIND OF	CUT & FILLED	PERFORATED	PURPOSE	
SIZE PER FOOT	PNR INCH	MAKE	AMOUNT	SHOE	FROM	FROM TO		
13" 40	8	Lapw.	3291					
7" 24	1						1	
· · · · ··· ·	·	· · · · · · · · · · · · · · · · · · ·			÷·······			
				<u> </u>	·····		·	
		• • • • • • •						
· ····· · ·····				_				
		<u>4k</u>	···· · ·		<u> </u>	······	i	

MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SPT	NO. SACKS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED
17-1/4"	13"	3291	300	Halliburton	Used 600# of	calcium chloride
9-7/8		- 33771	335-	-Halliburton		

		P	LUGS AND AD	APTERS			
Heaving n	lug-Material				Denth Se	t	
Heaving plug—Material Adapters—Material							
-		RECORD OF SHO	OOTING OR CH	HEMICAL 2	TREATMENT		
SIZE	SHELL USED	EXPLOSIVE OR CHEMICAL USED	QUANTITY	DATE	DEPTH SHOT OR TREATED	DEPTH CLEANED OUT	
						·	
Results of	shooting or cher	nical treatment				·	
		RECORD OF	DRILL-STEM A	ND SPECIA	AL TESTS		
If drill-ster	n or other specis	al tests or deviation s	surveys were ma	ide, submit	report on separate	sheet and attach hereto.	
			TOOLS US	ED			
Rotary too	ls were used fr	omOIfeet	to	_feet, and	from	feet tofeet	
Cable tool	s were used fr	om_ 3381! feet	to 3713'	_feet, and	from	feet tofeet	
			PRODUCTI	ON			
Put to pro	ducingDR	C HOLE					
The produc	tion of the first 2	24 hours was	barr	els of fluid o	of which	% was oil;%	
emulsion;	%	water; and	~ sedimen	t. Gravity,	Be		
If gas well	, cu, ft. per 24 h	ou r s	Gall	ons gasoline	e per 1.000 cu. ft. o	f gas	
Rock press	ure, lbs. per sq.	io	······································				
			EMPLOYE	ES			
			, Driller			Driller	
			Driller			Driller	
			ON DECODD C	N OTHER	GIDE		
			ON RECORD C				
					te and correct rec	ord of the well and all	
work done	on it so far as (an be determined fr	om available rec	eords.			
			^				
Subscribed	and sworn to be	fore me this 2 3		Tul sa Place	, Oklahoma	May 20, 1938	

day (эf.
-------	-----

FORMATION RECORD

.

;:

FROM	TO	THICKNESS IN FEET	FORMATION
0'	270' 469 696 855 966 982 988 1089 1176 1249 1364		Sand & calechi Red bed Red bed & shale Red bed & shells Red bed Anhydrite Hard sand Red bed & sand rock Red rock & sand shells Anhydrite Anhydrite & salt shells
	1474 1569 1672 1770 2059 2186 2324 2433 2518 2566 2615		Anhydrite & salt Salt & anhydrite shells Anhydrite & salt shells Salt & Anhydrite Salt & anhydrite shells Salt & shells Salt & shells Salt & anhydrite Anhydrite, broken salt & red rock S Anhydrite Anhydrite & red rock
Drilled to	2663 2687 2774 3117 3381 3397 3415 3617 3635 3642 3651 3673		Anhydrite & gyp Anhydrite & gyp Anhydrite & gyp Anhydrite & gyp Lime Lime & gyp Lime Lime & shele Lime Hard lime Lime & sand Lime Shale Sand & lime shells Lime Plugged back to 3686', total depth.
		· · · · ·	
		1	

1.1 i Line and Constant and the second 1 (s - 1) - 1 e da comencia de la c aan Coadder steel and an article of the and the second second n a star a st in in the sec

and the second second second second