COPY IO OF 1-CM-FOREMAN 5-USGS, HOBBS 1-FILE 1-R. J. STARRAK-TULS Form Approved. 1-BH, FIELD CLERK 1-A. B. CARY-MIDLAN Budget Bureau No. 42-R1424 Dec. 1973 1-MYM, ENGINITED STATES 5. LEASE DEPARTMENT OF THE INTERIOR *LC-032452* (a) 6. IF INDIAN, ALLOTTEE OR TRIBE NAME **GEOLOGICAL SURVEY** 7. UNIT AGREEMENT NAME SUNDRY NOTICES AND REPORTS ON WELLS Skelly Penrose "A" Unit (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9–331–C for such proposals.) 8. FARM OR LEASE NAME gas \mathbf{x} well other well 9. WELL NO. 2. NAME OF OPERATOR 54 Getty Oil Company 10. FIELD OR WILDCAT NAME 3. ADDRESS OF OPERATOR Langlie Mattix P. O. Box 730, Hobbs, New Mexico 88240 11. SEC., T., R., M., OR BLK. AND SURVEY OR 4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 Sec. 10, T-23S, R-37E AT SURFACE: Ltr. K, 1980' FSL & 1980' FWL 12. COUNTY OR PARISH 13. STATE AT TOP PROD. INTERVAL: MI AT TOTAL DEPTH: 14. API NO. 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA 15. ELEVATIONS (SHOW DF, KDB, AND WD) 3297' DF SUBSEQUENT REPORT OF: REQUEST FOR APPROVAL TO: TEST WATER SHUT-OFF FRACTURE TREAT SHOOT OR ACIDIZE REPAIR WELL (NOTE: Report results of multiple completion or zone PULL OR ALTER CASING change on Form 9-330.) MULTIPLE COMPLETE CHANGE ZONES ABANDON* Deepen, set liner, perf., & treat (other) 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* 10-10 to 11-7-78 - Pulled rods and thg. Pulled 51 liner. Drilled to new TD-3657'. 11-8-78 - Schlumberger ran Sonic Bore Hole Caliper Log 3650-1600'. 4 1/2" liner 3187-3656'. 11-9-78 - Dowell cemented 4 1/2" liner with 200 sxs Class "C", 2% CaCl, and 10# salt. Displaced cement 3655'. Reversed out. 11-10-78- Dowell cemented 4 1/2" liner with 150 sxs Class "C" with 2% CaCl. Displaced to 3137'. 11-13-78- Tested top of liner with 500# C.K. (CONTINUED) Subsurface Safety Valve: Manu. and Type _. Set @ 18. I hereby certify that the foregoing is true and correct Area Supt. 12-21-78 DATE SIGNED (This space for Federal or State office use) APPROVED BY TITLE CONDITIONS OF APPROVAL, IF ANY:

DE/

*See Instructions on Reverse Side

S. GEOLOGICAL SURVE MOJOS, NEW MEXICO