Submit 3 Copies to Approriate District

DISTRICTI

Apache Corporation

Unit Letter

State of New Mexico E....gy, Minerals and Natural Resouces

<u>DISTRICT I</u>		FORM C-103		
1625 N. French Dr., Hobbs, NM 88240		Revised March 25, 1999		
<u>DISTRICT II</u>	OIL CONSERVATION DIVISION	WELL API NO.		
811 South First, Artes1a, NM 88210	2040 South Pacheco	30-025-10704		
DISTRICT III	Santa Fe, NM 87505	5. Indicate Type of Lease		
1000 Rio Brazos Rd., Aztec, NM 87410	, , , , , , , , , , , , , , , , , , ,	☐ STATE FEE		
<u>DISTRICT IV</u>		6. State Oil & Gas Lease No.		
2040 South Pacheco, Santa Fe, NM 87505				
SUNDRY NOTICES AND REPORTS ON WELLS				
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH		7. Lease Name or Unit Agreement Name		
PROPOSALS.)		Skelly Penrose 'A' Unit		
Type of Well:		<u> </u>		
☑ OIL WELL	GAS WELL OTHER			
2. Name of Operator		8. Well No.		
Apache Corporation		50		

1980

. Pool name or Wildcat

Feet From The

Langlie-Mattix; 7 Rvrs-Q-Grayburg (37240)

West

10 23S 37E Section Township Range NMPM Lea County 10. Elevation (Show whether DF, RKB, RT, GR, etc.) 32841 Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data 11 NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF: Perform Remedial Work Remedial Work ✓ Plug and Abandon Altering Casing Temporarily Abandon Change Plans Commence Drilling Operations Plug and Abandonment Pull or Alter Casing Casing Test and Cement Job Other Other

Line and

12. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

North

1.) Perforate 7" casing @ 1225'

2000 Post Oak Blvd., Ste. 100, Houston, Texas 77056-4400

1980

Feet From The

- 2.)
- Set Cement Retainer @ 1195'

- THE COMMISSION MUST BE NOTIFIED 24 MOURS PRIOR TO THE PRINTING OF PLUGGE AGE COMMATIONS FOR THE CHOS CONTRACTOR # OT
- 3.) Cement squeeze behind 7" casing circulating to surface w/ 300 sx
- 4.) Top Cement Retainer @ 1195' w/ 35 sx
- 5.) Spot cement plug from 175' to surface w/ 100 sx
- 6.) Install P&A marker

I hereby certify that the information above is true and complete to the best of m	y knowledge and belief.				
SIGNATURE OD O	Now	TTTLE	Sr. Engineering Technician	DATE	5/31/00
TYPE OR PRINT NAME Debra J. Anderson			TEL	EPHONE NO.	713-296-6338
(This space for State Vse)					
APPROVED BY	TITLE		DA	TE	
CONDITIONS OF APPROVAL, IF ANY:					
					· ·