



QUINTUPLICATE

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

HOPE'S OFFICE 600

WELL RECORD

Mail to District Office, Oil Conservation Commission, to which Form C-101 was sent not later than twenty days after completion of well. Follow instructions in Rules and Regulations of the Commission. Submit in QUINTUPLICATE. If State Land submit 6 Copies

AREA 640 ACRES
LOCATE WELL CORRECTLY

Reaser & S heldon
(Company or Operator)

Kelly State
(Lease)

Well No. 3, in SW 1/4 of SW 1/4, of Sec. 16, T. 23, R. 37, NMPM.

Langlie-Mattix

Pool,

Lea

County.

Well is 660 feet from south line and 660 feet from west line

of Section 16. If State Land the Oil and Gas Lease No. is 8-4958

Drilling Commenced July 5, 1956. Drilling was Completed July 29, 1956.

Name of Drilling Contractor Carper Drilling Company

Address Carper Bldg., Artesia, New Mexico

Elevation above sea level at Top of Tubing Head 3332'. The information given is to be kept confidential until , 19.

OIL SANDS OR ZONES

No. 1, from 3555' to 3568' No. 4, from to

No. 2, from 3581' to 3588' No. 5, from to

No. 3, from 3609' to 3617' No. 6, from to

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from to feet.

No. 2, from to feet.

No. 3, from to feet.

No. 4, from to feet.

CASING RECORD

SIZE	WEIGHT PER FOOT	NEW OR USED	AMOUNT	KIND OF SHOE	CUT AND PULLED FROM	PERFORATIONS	PURPOSE
10 3/4			1107				
7	20	New	3627				

MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED
8 3/4	7	3627	600	Halliburton		

RECORD OF PRODUCTION AND STIMULATION

(Record the Process used, No. of Qts. or Gals. used, interval treated or shot.)

Sand oiled individually with 10,000 gallons lease crude with 1/10th pound per gallon adomite added and 20,000 lbs. sand each of three zones which were bullet perforated with 2 shots per foot 3609-17', 3581-88' 3555-68'.

Result of Production Stimulation Increased production to 60 BOPD

Depth Cleaned Out 3624'

CORD OF DRILL-STEM AND SPECIAL TT 1

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto

TOOLS USED

Rotary tools were used from 0 feet to 3627 feet, and from feet to feet.
Cable tools were used from feet to feet, and from feet to feet.

PRODUCTION

Put to Producing August 1, 1956
OIL WELL: The production during the first 24 hours was 60 barrels of liquid of which 100 % was oil; % was emulsion; % water; and % was sediment. A.P.I. Gravity 40
GAS WELL: The production during the first 24 hours was M.C.F. plus barrels of liquid Hydrocarbon. Shut in Pressure lbs.
Length of Time Shut in

PLEASE INDICATE BELOW FORMATION TOPS (IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE):

Southeastern New Mexico

Northwestern New Mexico

T. Anhy.	T. Devonian	T. Ojo Alamo
T. Salt.	T. Silurian	T. Kirtland-Fruitland
B. Salt. 2420'	T. Montoya	T. Farmington
T. Yates. 2600'	T. Simpson	T. Pictured Cliffs
T. 7 Rivers	T. McKee	T. Menefee
T. Queen. 3310'	T. Ellenburger	T. Point Lookout
T. Grayburg	T. Gr. Wash	T. Mancos
T. San Andres	T. Granite	T. Dakota
T. Glorieta	T.	T. Morrison
T. Drinkard	T.	T. Penn
T. Tubbs	T.	T.
T. Abo	T.	T.
T. Penn	T.	T.
T. Miss	T.	T.

FORMATION RECORD

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
SEE LOG AMERADA STATE PB# 1. THE OLD AMERADA WELL RE*ENTERED.							

ATTACH SEPARATE SHEET IF ADDITIONAL SPACE IS NEEDED

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

July 31, 1956 (Date)
Company or Operator Reaser & Sheldon Address 302 Carper Bldg., Artesia, New Mex.
Name Victor P. Sheldon Position or Title Partner