


OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

MISCELLANEOUS REPORTS ON WELLS



HOBBS OFFICE

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut-off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below:

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL		REPORT ON PULLING OR OTHERWISE ALTERING CASING	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF		REPORT ON DEEPENING WELL	<input checked="" type="checkbox"/>
REPORT ON RESULT OF PLUGGING OF WELL			

Monument, New Mexico

Place

April 18, 1946

Date

OIL CONSERVATION COMMISSION,
SANTA FE, NEW MEXICO.

Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the

Amerada Petroleum Corporation State PR Well No. 1 in the
Company or Operator Lease

SW 1/4 of SW 1/4 of Sec. 16, T. 23S, R. 37E, N. M. P. M.,
Harrison Field, Lee County.

The dates of this work were as follows: March 18, to March 25, 1946Notice of intention to do the work ~~was~~ (was not) submitted on Form C-102 on _____ 19__and approval of the proposed plan ~~was~~ (was not) obtained. (Cross out incorrect words.)

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

5076' Drilled out depth. Drilled to ~~5127'~~ and ran Halliburton drill stem test with packer set at 5076' and recovered 155' Oil 1735' of sulphur water and drilled deeper to 5151' and Halliburton drill stem test with packer set at 5131' and recovered 90' Oil and 60' of water, reran Halliburton drill stem test with packer set at 5131' and recovered 90' oil and 490' of sulphur water and plugged back to 5105' with 15 Sax Incor cement, ran Tubing set at 5082' and Packer set at 5070' and swabbed 67.70 barrels of sulphur water in 21 hours. Preparing to set another cement retainer and squeeze well again.

Witnessed by Don Topper Name Amerada Pet. Corp. Asst. Dist. Supt.
Company Title

Subscribed and sworn before me this _____

I hereby swear or affirm that the information given above is true and correct.

18 day of April, 1946Name Don TopperPosition Asst. Dist. Supt.Representing Amerada Pet. Corp.
Company or Operator

My commission expires _____

Address Drawer D, Monument, New Mexico.

Remarks:

APPROVED

Date APR 27 1946

Ray J. Yorkrough
Name
Oil & Gas Inspector
Title