

NEW

XICO OIL CONSERVATION COM

SI

Santa Fe, New Mexico

## MISCELLANEOUS NOTICES

JAN 2 1946

Submit this notice in triplicate to the Oil Conservation Commission or its proper agent before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or its agent, of the plan submitted. The plan as approved must be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of notice by checking below:

NOTICE OF INTENTION TO TEST CASING SHUT-OFF		NOTICE OF INTENTION TO SHOOT OR CHEMICALLY TREAT WELL	
NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO PULL OR OTHERWISE ALTER CASING	
NOTICE OF INTENTION TO REPAIR WELL		NOTICE OF INTENTION TO PLUG WELL	
NOTICE OF INTENTION TO DEEPEN WELL		REQUEST TO PRODUCE BONUS DISCOVERY WELL ALLOWABLE	X

Monument, New Mexico

December 11, 1945

OIL CONSERVATION COMMISSION,

Santa Fe, New Mexico.

Gentlemen:

Following is a notice of intention to do certain work as described below at the

Amerada Petroleum Corporation, State PB Well No. 1 in SW SW  
 Company or Operator Lease  
 of Sec. 16, T. 23S, R. 37E, N. M. P. M., Penrose Skelly Field,  
Lea County.

## FULL DETAILS OF PROPOSED PLAN OF WORK

FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS OF THE COMMISSION

Total Depth 5075', 5 1/2" Casing set at 5075' and cement drilled out to 5066' and gun perforated 5058 to 5065' November 2, 1945 and with 48 shots. Gun perforated from 5015 to 5058' with 172 shots, November 12, 1945.

Elevation 3332' Derrick Floor, and 3322' Ground.

Top Anhydrite 1070'

Base of Salt 2420'

Top of Yates 2600'

Zone 4 3865'

Base San Andres 4965'

Pay 5015' to 5065' Acidized with 3000 Gals Dowell Acid.

2" EUE Tubing set at 5059' Flowed 155.91 Bbls Oil, 77.22 Bbls Water swab and flow for 21 hours. Gas-Oil-Ratio 511.

10 3/4" Casing set at 1107'

7 5/8" Casing set at 3754' and drilled out cement to 3709, gun perforated 3644 to 3704'

September, 14, gun perforated 3644' to 3692' with 96 shots September 23, gun perforated from 3610 to 3644 with 136 shots September 29, 1945 and test sulphur water and drilled deeper.

Approved 28 December, 1945

except as follows:

*for 25,075 bbls.  
 effective 1 Jan. '46*

Amerada Petroleum Corporation  
 Company or Operator

By

Position Asst. Dist. Supt.

Send communications regarding well to

Name Amerada Pet. Corp.,Address Drawer B,Monument, New Mexico.

OIL CONSERVATION COMMISSION,

By

Title

*R. R. Spurrer  
 Director*

