

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)Form approved.
Budget Bureau No. 42-R1424.
5. LEASE DESIGNATION AND SERIAL NO.

LC 054453

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

James H. Duthie Bty 2

9. WELL NO.

3

10. FIELD AND POOL, OR WILDCAT

Langlie Mattix-7R

Jalmat-Vates

11. SEC., T., R., M., OR BLM. AND
SURVEY OR AREA

Sec. 18, T23S, R37E

12. COUNTY OR PARISH

Lea

13. STATE

N.M.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1.

OIL
WELL ☐GAS
WELL ☐

OTHER

P & A

2. NAME OF OPERATOR

Atlantic Richfield Company

3. ADDRESS OF OPERATOR

P. O. Box 1978, Roswell, New Mexico 88201

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

1980' FSL & 660' FEL (Unit Letter I)

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3319' GR

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

X

(Note: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

On 7/2/71 spotted 30 sx cement from 3576' to 3376' and 50 sx cement from 2850' to 2500'. On 7/3/71 shot off and recovered 5½" 14# casing @ 1533'. Laid down 39 jts. Spotted 35 sack Class A cement plug 1478-1578'. Spotted 35 sk Class A cement plug 1073-1173'. Put 10 sk cement plug in top of well. Installed dry hole marker. Well P & A 7/5/71. 8-5/8" casing remains intact. 9#/gal salt gel mud was used to spot all plugs.

Your office will be notified when this location is ready for inspection.

18. I hereby certify that the foregoing is true and correct

SIGNED

D.D. Lutes

TITLE Dist. Drlg. Supervisor

DATE

8/10/71

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

APPROVED

DATE

*See Instructions on Reverse Side

J L GORDON
DISTRICT ENGINEER