

NEW MEXICO OIL CONSERVATION COMMISSION

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

5a. Indicate Type of Lease
State Fee

5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO REPERFORATE OR PLUG BACK TO A DIFFERENT RESERVOIR. USE APPLICATION FOR PERMIT - C-103 (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL GAS WELL OTHER

2. Name of Operator
Getty Oil Company

3. Address of Operator
P. O. Box 1351 Midland, Texas 79702

4. Location of Well
UNIT LETTER **A** **660** FEET FROM THE **North** LINE AND **660** FEET FROM
THE **East** LINE, SECTION **20** TOWNSHIP **23S** RANGE **37W** N.M.P.M.

15. Elevation (Show whether DF, RT, GR, etc.)
3326' DF

7. Unit Agreement Name

8. Farm or Lease Name
J. C. Johnson Bty. 2

9. Well No.
2

10. Field and Pool, or Wildcat
Langlie-Mattix

12. County
Lea

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input checked="" type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

1. Move in workover rig. Pull rods and tubing.
2. Set 150 sack cement plug 2833-3559'.
3. Perforate 7" OD casing at 2400' with 2 holes.
4. Cement squeeze perfs. 2400' with sufficient cement to provide 200' of cement outside casing and a 200' plug inside casing 2200-2400'.
5. Set 40 sack cement plug 1100-1300'.
6. Set 10 sack cement plug to surface.
7. Install dry hole marker.

All casing strings will be left in the hole. All intervals not cemented will be filled with 10.2% mud.

THE COMMISSION MUST BE NOTIFIED 24 HOURS PRIOR TO THE BEGINNING OF REPAIRING OPERATIONS FOR THE C-103 TO BE APPROVED.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED (signed) D. R. Crow D. R. Crow TITLE Lead Clerk DATE 2-22-77

APPROVED BY Jerry Sexton TITLE _____ DATE _____
Dist 1, Supv.

FEB 24 1977

Expired 5/24/77

CONDITIONS OF APPROVAL, IF ANY:

RECEIVED

FEB 23 1977

OIL CONSERVATION COMM.
HOBBS, N. M.