



STATE OF NEW MEXICO
ENERGY, MINERALS AND NATURAL RESOURCES DEPARTMENT
OIL CONSERVATION DIVISION
HOBBS DISTRICT OFFICE

GARREY CARRUTHERS
GOVERNOR

December 30, 1988

POST OFFICE BOX 1980
HOBBS, NEW MEXICO 88241-1980
(505) 393-6161

Penroc Oil Corporation
P.O. Box 5970
Hobbs, NM 88240

Re: Recompletion to Jalmat T-Y-SR Pool
J.C. Johnson #5-C
Sec. 20, T23S, R37E

Dear Merch:

The recompletion of the above-referenced well from the Langlie Mattix to a Jalmat oil well will require that the 320-acre NSP-559 be reduced to 280 acres.

An oil allowable is being assigned to the #5 well and you should make application to our Santa Fe office for the reduction of NSP-559 to 280 acres as soon as possible.

Very truly yours,

OIL CONSERVATION DIVISION

Jerry Sexton
Supervisor, District I

ed

WRS COMPLETION REPORTCOMPLETIONS SEC 20 TWP 23S RGE 37E
PI# 30-T-0014 01/30/89 30-025-10812-0001 PAGE 1NMEX LEA * 660FNL 2160FWL SEC NE NW
STATE COUNTY FOOTAGE SPOT
PENROC OIL D X DO
OPERATOR WELL CLASS INIT FIN
5 JOHNSON J C
WELL NO. LEASE NAME
3307DF JALMAT
OPER ELEV FIELD POOL AREA
API 30-025-10812-0001LEASE TYPE NO. PERMIT OR WELL I.D. NO.
06/07/1988 06/18/1988 WO-UNIT OIL-WO
SPUD DATE COMP DATE TYPE TOOL STATUS
3000 YTS-SVRV NOT RPTD
PROJ DEPTH PROJ FORM CONTRACTOR
DTD 3640 PB 3000 OTD 3640 FM/TD QUEEN
DRILLERS T.D. LOG T.D. PLUG BACK TO OLD T.D. FORM T.D.**LOCATION DESCRIPTION**

10 MI S EUNICE, NM

TUBING DATA

TBG 2 3/8 AT 2950

INITIAL POTENTIALIPP 17BOPD 54 MCFD 1BW 24HRS
YTS-SVRV PERF W/ 2/FT 2847- 2958
PERF 2847- 2958
ACID 2847- 2958 1500GALS
15% HCL
SWFR 2847- 2958 40000GALS 49000LBS SAND
18000 LBS 20/40
31000 LBS 12/20
GTY 34.1 GOR 3176

ADDTVGELA

PRODUCTION TEST DATAQUEEN OPENHOLE 3398- 3607
OPEN 3398- 3607
BRPG @ 3000 3398- 3607**DRILLING PROGRESS DETAILS**PENROC OIL
BOX 5315

CONTINUED IC# 300257001689

COMPLETIONS
PI# 30-T-0014 01/30/89 SEC 20 TWP 23S RGE 37E
30-025-10812-0001 PAGE 2

PENROC OIL
5

JOHNSON J C

D X DO

DRILLING PROGRESS DETAILS

HOBBS, NM 88240
505-397-3596

OWWO: OLD INFO: FORMERLY SKELLY OIL #1 LANGLIE
MATTIX. SPUD 6/4/54. 8 5/8 @ 1120 W/300 SX,
5 1/2 @ 3398 W/200 SX. LOG TOPS: YATES 2614,
SEVEN RIVERS 2868, QUEEN 3307. OTD 3640. PB
3607. COMP 8/8/54. IPF 10 BOPD. PROD ZONE:
QUEEN 3398-3607 (OPENHOLE).
01/23 LOC/1989/
01/23 3640 TD, PB 3000
COMP 6/18/88, IPP 17 BO, 54 MCFG, 1 BWPD,
GOR 3176, GTY 34.1
PROD ZONE - YATES-SEVEN RIVERS 2847-2958
FIRST REPORT & COMPLETION