

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEYSUBMIT IN TRIPPLICATE  
(Other Instructions on  
reverse side)Form approved,  
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

LC-030187

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

C. E. LaMunyon

9. WELL NO.

5

10. FIELD AND POOL, OR WILDCAT

Langlie Mattix

11. SEC., T., R., M., OR BLK. AND  
SURVEY OR AREA

Sec 21, 23-S, 37-E

12. COUNTY OR PARISH

Lea

13. STATE  
New Mexico1. OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR

Gulf Oil Corporation

3. ADDRESS OF OPERATOR

Box 670, Hobbs, New Mexico 88240

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.\*  
See also space 17 below.)  
At surface

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3325' DF

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

## NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐(Other) ☐PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐ABANDON\* ☐CHANGE PLANS ☐

## SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐FRACTURE TREATMENT ☐SHOOTING OR ACIDIZING ☐(Other) \*Corrected Report. ☐REPAIRING WELL ☐ALTERING CASING ☐ABANDONMENT\* ☒ \*(NOTE: Report results of multiple completion on Well  
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

3709' TD.  
Ran 4-1/2" bit and casing scraper to 3520'. Set CI BP at 3500' and capped with 4 sacks of cement, abandoning open hole interval 3535' to 3709'. Loaded hole with abandonment mud. Perforated 5-1/2" casing with 5 holes at 2600'. Set cement retainer at 2495' and squeezed below retainer with 50 sacks of Class C cement. Spotted 4 sacks of cement on top of retainer. Loaded hole with abandonment mud. Perforated 5-1/2" casing at 1170' with 5 circular holes. Set retainer at 1082'. Circulated 50 sacks of cement inside and outside 5-1/2" casing below retainer. Spotted 4 sacks of cement on top of retainer. Loaded hole with abandonment mud. Spotted 6 sack cement plug from 55' to surface. Installed dry hole marker. Cleaned location. Plugged and abandoned November 29, 1975. Well is now ready for your final inspection.

18. I hereby certify that the foregoing is true and correct

SIGNED D. F. BerlinTITLE Area EngineerDATE December 5, 1975

(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_

TITLE \_\_\_\_\_

CONDITIONS OF APPROVAL, IF ANY:

APPROVED

JAN 6 1976  
ARTHUR R. BROWN  
DISTRICT ENGINEER

\*See Instructions on Reverse Side