

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUBMIT IN TRIPL.  
(Other instructions  
verse side)

Form approved.  
Budget Bureau No. 42 R1424.

5. LEASE DESIGNATION AND SERIAL NO.

LC-030187

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

C. E. LaMunyon

9. WELL NO.

5

10. FIELD AND POOL, OR WILDCAT

Langlie Mattix

11. SEC., T., R., M., OR BLK. AND  
SURVEY OR AREA

Sec 21-23-S, 37-E

12. COUNTY OR PARISH 13. STATE

Lea

New Mexico

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR

Gulf Oil Corporation

3. ADDRESS OF OPERATOR

Box 670, Hobbs, New Mexico 88240

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.\*  
See also space 17 below.)  
At surface

660' FN & WL, Section 21, 23-S, 37-E.

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3325' DF

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐

PULL OR ALTER CASING ☐

WATER SHUT-OFF ☐

REPAIRING WELL ☐

FRACTURE TREAT ☐

MULTIPLE COMPLETE ☐

FRACTURE TREATMENT ☐

ALTERING CASING ☐

SHOOT OR ACIDIZE ☐

ABANDON\* ☐

SHOOTING OR ACIDIZING ☐

ABANDONMENT\* ☐

REPAIR WELL ☐

CHANGE PLANS ☐

(Other) ☐

(Other) Plug and Abandon

(NOTE: Report results of multiple completion on Well  
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

3709' TD.

Set CI BP at 3500' and cap with 5 sacks, 48', of Class C cement to 3452', abandoning open hole interval 3535' to 3709'. Spot 20 sacks, 195', Class C cement plug from 1266' to 1071', across top of salt at 1216' and across 8-5/8" shoe at 1121'. Spot 6 sack Class C cement plug from 50' to surface. Install dry hole marker and clean location.

**STIPULATION:** Since our records indicate cement behind the 5 1/2" casing did not fill to above 2800 feet, approval of this notice is subject to the following in addition to the proposed top and bottom plugs:

Cut and pull 5 1/2" casing from below 2600 feet and place additional 100 foot (25 sack minimum) in intervals 2500 to 2600 and 1070 to 1170 feet, or perforate 5 1/2" casing and place cement outside and inside 5 1/2" casing through these intervals.

18. I hereby certify that the foregoing is true and correct

SIGNED

*B. J. Barker*

TITLE

Area Engineer

DATE

June 26, 1975

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

\*See Instructions on Reverse Side