

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

MISCELLANEOUS NOTICES

Submit this notice in TRIPLICATE to the District Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL		NOTICE OF INTENTION TO DRILL DEEPER	
NOTICE OF INTENTION TO PLUG WELL		NOTICE OF INTENTION TO PLUG BACK	<input checked="" type="checkbox"/>	NOTICE OF INTENTION TO SET LINER	
NOTICE OF INTENTION TO SQUEEZE		NOTICE OF INTENTION TO ACIDIZE		NOTICE OF INTENTION TO SHOOT (Nitro)	
NOTICE OF INTENTION TO GUN PERFORATE		NOTICE OF INTENTION (OTHER) <u>Fracture treat</u>	<input checked="" type="checkbox"/>	NOTICE OF INTENTION (OTHER)	

OIL CONSERVATION COMMISSION
SANTA FE, NEW MEXICOHobbs, New Mexico
(Place)September 30, 1957
(Date)

Gentlemen:

Following is a Notice of Intention to do certain work as described below at the.....

Gulf Oil Corporation Saltmount Well No. 1 in P (Unit)
(Company or Operator) Lease
SE 1/4 SE 1/4 of Sec. 21, T. 23-S, R. 37-E, NMPM., Teague Pool
(40-acre Subdivision)
Lea County.

FULL DETAILS OF PROPOSED PLAN OF WORK
(FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

In order to increase production it is proposed to plug back and fracture treat as follows:

1. Pull tubing and packer. Run steel line measurement, if warranted clean out.
2. Set bridge plug on electric line in interval from 9445-9455', plug back with Hydromite to 9440'.
3. Run 2-7/8" tubing open ended with full bore packer. Spot 500 gallons mud acid on perforations and squeeze into formation. Set packer above perforations. Treat formation with 10,000 gallons gelled lease oil with 1# sand per gallon. Block fractured zone with crushed mothballs. Treat formation with 10,000 gallons gelled lease oil with 1# sand per gallon. Pull tubing and packer. Run 2-3/8" tubing with hookwall packer and flow valves and return well to production.

Approved....., 19.....
Except as follows:Approved
OIL CONSERVATION COMMISSIONBy.....
Title.....Gulf Oil Corporation

Company or Operator

By.....

Position Area Supt. of Prod.

Send Communications regarding well to:

Gulf Oil Corporation

Name.....

Address Box 2167, Hobbs, New Mexico