

LC 030186(6)

SUNDRY NOTICES AND REPORTS

Do not use this form for any purpose other than that for which it was designed. Use "A" SECTION FOR PERMITS and such proposals.

1. ☐ OIL WELL ☐ GAS WELL ☐ OTHER	7. UNIT AGREEMENT NAME
2. NAME OF OPERATOR Wolffson Oil Company	8. FARM OR LEASE NAME Cline Federal
3. ADDRESS OF OPERATOR c/o Hobbs Pipe & Supply Co., Box 2010, Hobbs, N. M. 88240	9. WELL NO. 5
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 990' FNL & 2315' FEL	10. FIELD AND POOL, OR WILDCAT
11. SEC., T., R., M., OR BLM. AND SURVEY OR AREA 22-23-37	12. COUNTY OR PARISH Lea
13. STATE N. M.	

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
TEST WATER SHUT-OFF ☐	WELL OR ALTER CASING ☐	WATER SHUT-OFF ☐	REPAIRING WELL ☐
FRACTURE TREAT ☐	MULTIPLE COMPLETE ☐	FRACTURE TREATMENT ☐	ALTERING CASING ☐
SHOOT OR ACIDIZE ☐	ABANDON* ☒	SHOOTING OR ACIDIZING ☐	ABANDONMENT* ☐
REPAIR WELL ☐	CHANGE PLANS ☐	(Other) ☐	

(Note: Report results of multiple completion or Well Completion or Recompletion Report and Log Form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of start, of any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

1. Spot a 100' plug to cover existing perms., 3590/3602, 3640/3654.
2. Load hole w/mud-laden fluids.
3. Shoot and bull casing from approximately 1500'.
4. Spot a 100' plug at casing stub.
5. Spot a 100' plug 50' in and out of surface casing at 625'.
6. Spot a 10 sx top-hole and erect a 4" regulation marker.

AMENDMENT:

1. Cement plug in step 1. above should be 20 sacks minimum and top of plug should be minimum of 100 feet above top perforation.
2. Place additional 20 sack plug inside 5 1/4" csg. in interval 2500-2650 feet.
3. Place plug in step 4. above in interval 950-1050 feet instead of in top of 5 1/4" stub, or an additional 100 foot cement plug in the interval 950-1050 feet.
4. Locations of other plugs are satisfactory.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

AGENT

DATE

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

APPROVED
AS AMENDED
OCT 26 1973
ARTHUR R. BROWN
DISTRICT ENGINEER

*See Instructions on Reverse Side