Form 9-881 a (Feb. 1951)

OBBS
(SUBMIT IN TRIPLICATE)

UNITED STATES DEPARTMENT OF THE INTERIOR **GEOLOGICAL SURVEY**

	Budget Bureau No. 42-R358.4. Approval expires 12-31-60.
Land O	ffice

Unit MAY 28 1959

U. S. GEOLOGICAL SURVEY

HOBBS, NEW MEXICO

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF.	
NOTICE OF INTENTION TO CHANGE PLANS NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR W		
NOTICE OF INTENTION TO SHOOT OR ACIDIZE		
NOTICE OF INTENTION TO PULL OR ALTER CASING		
NOTICE OF INTENTION TO ABANDON WELL		
(INDICATE ABOVE BY	CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)	
	Fey 28, 1959	, 19
A Amyron ?ederal		
Vell No. 3 is located 36%	ft. from $\binom{N}{W}$ line and 20 ft. from $\binom{N}{W}$ line of sec.	
	(W)	
34/4 ist/4 Sec. 28 1231	NYE KWE	
(½ Sec. and Sec. No.) (Tw	p.) (Range) (Meridian)	
(Field)	(County or Subdivision) (State or Territory)	
itate names of and expected depths to objective sa ing poi	nds; show sizes, weights, and lengths of proposed casings; indicate mudding jo ints, and all other important proposed work)	bs, cen
ing poi	ints, and all other important proposed work)	bs, cen
intend to drill with rotary t	ints, and all other important proposed work)	bs, cen
intend to drill with rotary t	ints, and all other important proposed work)	ba, cen
intend to drill with rotary t and at approximate depth of	ints, and all other important proposed work)	
intend to drill with rotary to send at approximate depth of will set 300° of 10-3/4" 320	ints, and all other important proposed work) bools(J. G. Hun Delg. Co.) to test Pengrase 3750*, casing progress as follows: cag to be circulated w/ approximately 175 as	
intend to drill with rotary to send at approximate depth of will set 300° of 10-3/4" 320	ints, and all other important proposed work) bools(J. G. Hun Delg. Co.) to test Pengrase 3750*, casing progress as follows: cag to be circulated w/ approximately 175 as	
intend to drill with rotary t sand at approximate depth of	ints, and all other important proposed work) boole(J. C. Sun Drig, Co.) to test Pengrape 3750*, cesting progress as follows: cag to be circulated w/ approximately 175 as	
intend to drill with rotary to send at approximate depth of ill set 300° of 10-3/4" 320	ints, and all other important proposed work) boole(J. C. Sun Drig, Co.) to test Pengrape 3750*, cesting progress as follows: cag to be circulated w/ approximately 175 as	
intend to drill with rotary to send at approximate depth of will set 300° of 10-3/4" 320	ints, and all other important proposed work) boole(J. C. Sun Drig, Co.) to test Pengrape 3750*, cesting progress as follows: cag to be circulated w/ approximately 175 as	
intend to drill with rotary to send at approximate depth of till set 300° of 10-3/4" 320	ints, and all other important proposed work) boole(J. C. Sun Drig, Co.) to test Pengrape 3750*, cesting progress as follows: cag to be circulated w/ approximately 175 as	
intend to drill with rotary to send at approximate depth of will set 300° of 10-3/4" 320° of 5-1/3" 146° cot 3750° cot 5-1/3" 146° cot 3750	ints, and all other important proposed work) bools(J. C. Hun Delg. Co.) to test Pengrase 3750', cooling progress as follows: eng to be circulated w/ approximately 175 es (approximately) and coment with 200 ex	•
intend to drill with rotary to send at approximate depth of will set 300° of 10-3/A° 326 will set 3750° of 5-1/2° 146 will set 3750°	bools (J. C. San Drig. Co.) to test Penrose 3750', cesting progress as follows: cag to be circulated w/ approximately 175 compromisedly 175 compromisedly 175 compromisedly 175 compromisedly 175 compromisedly 175 compromisedly) and commit with 200 cm	•
intend to drill with rotary to cond at approximate depth of will set 300° of 10-3/4° 320° of 5-1/2° 140° and at 1750° of 5-1/2° 140° and at 1750° of 5-1/2° 140° and at this plan of work must receive the company do to the set 300° and at 100° and	bools (J. C. Sun Brig. Co.) to test Penrope 3750', cesting progress as follows: cog to be circulated w/ approximately 175 compromisedly 175 compromisedly 175 compromisedly 175 compromisedly) and commit with 200 cm.	•
intend to drill with rotary to send at approximate depth of will set 300° of 10-3/4" 320° of 5-1/3" 146° cot 3750° cot 5-1/3" 146° cot 3750	bools (J. C. Sun Brig. Co.) to test Penrope 3750', cesting progress as follows: cog to be circulated w/ approximately 175 compromisedly 175 compromisedly 175 compromisedly 175 compromisedly) and commit with 200 cm.	•
intend to drill with rotary to send at approximate depth of fill set 300° of 10-3/4° 32° ill set 3750° of 5-1/2° 140° ill set 3750° of 5-1/2° ill set 3750° ill set 3750° of 5-1/2° ill set 3750° ill set 3	bools (J. C. Num Delg. Co.) to test Pengross 3750', cesing progress as follows: eng to be circulated w/ approximately 175 as (approximately) and coment with 200 ax e approval in writing by the Geological Survey before operations may be commit in R. Rill.	•
intend to drill with rotary to cond at approximate depth of fill set 300° of 10-3/A° 326 ill set 3750° of 5-1/2° 146 Lunderstand that this plan of work must receive the set 300° of	bools (J. C. Num Delg. Co.) to test Pengross 3750', cesing progress as follows: eng to be circulated w/ approximately 175 as (approximately) and coment with 200 ax e approval in writing by the Geological Survey before operations may be commit in R. Rill.	•
intend to drill with rotary to send at approximate depth of fill set 300° of 10-3/A° 32° Mill set 3750° of 5-1/2° 14° Mill set 3750° of 5-1/2° Mill set 3750° of	bools (J. C. Num Delg. Co.) to test Pengross 3750', cesing progress as follows: eng to be circulated w/ approximately 175 as (approximately) and coment with 200 ax e approval in writing by the Geological Survey before operations may be commit in R. Rill.	•

APPROVED