Form 9-381 a (March 1942)

(SUBMIT IN TRIPLICATE)

COPY

Budges Bureau No. 42-R358.1. Approval expires 11-50-49.

Land Office Las Cruces

APPROVED: February 18, 1949

/s/ M. G. Soyster DISTRICT ENGINEER UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

Land Omce	
Land	030187
ML APR	
	8 19/-
HODE	o love
HOBBS	OF U

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF SHOUTING OR ACTULING.	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO PULL OR ALTER CASING		
 NOTICE OF INTENTION TO ABANDON WELL		

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

			February 16,	_, 19 <u>.49</u>
LaMunyon Well No8 is loc	ated <u>660</u> ft.	from ${S \\ S}$ line an	ad <u>1980</u> ft. from $\left\{ \begin{matrix} \mathbf{K} \\ \mathbf{W} \end{matrix} \right\}$ line of se	c. <u>22</u>
SW of 22	235	37E	NMPM	
(1/4 Sec. and Sec. No.)	(Twp.)	(Range)	(Meridian)	
Teague	L	ea	New Mexico	
(Field)	(County or Subdivision)		(State or Territory)	

The elevation of the derrick floor above sea level is <u>3296'</u> ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

After waiting forty-eight hours, the 9-5/8" casing was tested with 1200# pressure applied for 30 minutes. The plug was drilled and the casing and cement were tested with 1200# pressure applied for 30 minutes. Both tests were OK, and preparations were made to drill ahead.

Top of cement back of 9-5/8" csg @ 1930' per temperature survey.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Gulf Oil Corporation

Address P. O. Box 1667

Hobbs, New Mexico

Title District Engineer

U. S. GOVERNMENT PRINTING OFFICE 10-8437-3

н Н

the second se