

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYN. M. OIL CORP. (HOBBS)
P. O. BOX 670
HOBBS, N. M. 88240
SUBMIT IN TRIPLICATE
(Other instructions on re-
verse side)Form approved
Budget Bureau No. 42-1111
5. LEASE DESIGNATION AND SERIAL NO.
LC-030187

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. NAME OF LEASE OWNER
La Munion Fed9. WELL NO.
1

10. FIELD AND TOWN, OR WILDCAT

Langley Mattie11. SEC., T., R., OR BLK. AND
SURVEY OR AREA**Sec 22-T235-R376**

12. COUNTY OR PARISH

Lea13. STATE
NM

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)1. ☒ OIL WELL ☐ GAS WELL ☐ OTHER2. NAME OF OPERATOR
Gulf Oil Corporation3. ADDRESS OF OPERATOR
P. O. Box 670, Hobbs, NM 882404. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.
See also space 17 below.)
At surface**2310' FSL + 2310' FWL**

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, CR, etc.)

3272' GL

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

RIHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETION

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting and proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

POH up production eqpt. set pkr @ 636', ppg on tbg + would not hold press. obtain circ out surf csg. 1st 5 1/2" prod csg 500#-held ok. set cmt ret @ 554', 1st csg 250#-held ok. Pmp 300 sil cl "C" w/ lach. Circ 10 sil cmt out 10 3/4-5 1/2 ann. close run on 10 3/4. Pmp 10 sil @ 700#. Drl cmt + cmt ret. Circ hole clean. G/H up pkr. 1st csg 322'-surf, would hold 500#. Could pmp into csg 322'-552' @ 1 BPM 900#. R/H w/ 2 3/8" tbg to 505'. ND BOP, NU WH. Kill P+A well.

18. I hereby certify that the foregoing is true and correct

SIGNED **RDPite**

TITLE

Area Engineer

DATE **10-27-83**

(This space for Federal or State office use)

APPROVED BY
CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

ACCEPTED FOR RECORD

OCT 31 1983

*See Instructions on Reverse Side

ROSWELL, NEW MEXICO