

Form 9-311
(May 1963)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPPLICATE
(Other instructions on re-
verse side)

Form approved
Budget Bureau No. 42-R1424
6. LEASE DESIGNATION AND SERIAL NO.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

LC-030187

7. IF INDIAN, ALLOTTEE OR TRIBE NAME

1. OIL WELL ☒ GAS WELL ☐ OTHER

7. UNIT AGREEMENT NAME

2. NAME OF OPERATOR
Gulf Oil Corporation

8. FARM OR LEASE NAME

LaMunyon Federal "B"

3. ADDRESS OF OPERATOR
P. O. Box 670, Hobbs, NM 88240

9. WELL NO.

3

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.
See also space 17 below.)
At surface

10. FIELD AND TOOL, OR WILDCAT

Langlie Mattix

660' FSL & 1980' FEL

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec 22-T23S-R37E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, CR, etc.)

3259' GL

12. COUNTY OR PARISH 13. STATE

Lea

NM

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

ABANDON OR ACIDIZE

REPAIR WELL

(Other) Repair Casing Leak

PULL OR ALTER CASING

MULTIPLE COMPLETION

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(Note: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any
proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones perti-
nent to this work.)

POH with production equipment. Locate casing leak with packer. Set cement
retainer 75' above leak, test tubing 3000# pressuring up backside to 500#.
Squeeze with 300 sacks Class "C" cement. Circulate cement out 10-3/4" - 5 1/2"
casing annulus. Dump 3 sacks cement on cement retainer. Drill cement retainer
and cement. Test casing 500#.

RECEIVED

JUN 2 1983

OIL & GAS

ROSWELL, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

RDP

TITLE Area Engineer

DATE 5-27-83

(This space for Federal or State office use)

APPROVED

APPROVED BY (Orig. Sgd.) PETER W. CHESTER

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

JUN 28 1983

*See Instructions on Reverse Side