

HOBBS SUBMIT IN TRIPLICATE)

UNITED STATES OFFICE DCC

GEOLOGICAL SURVEY
1959 AUG 31 PM

NOTICE OF INTENTION TO DRILL		SUBSEQUENT REPORT OF WATER SHUT-OFF	
NOTICE OF INTENTION TO CHANGE PLANS		SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF		SUBSEQUENT REPORT OF ALTERING CASING	
OTICE OF INTENTION TO RE-DRILL OR REPAIR WELL		SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE		SUBSEQUENT REPORT OF ABANDONMENT	,
NOTICE OF INTENTION TO PULL OR ALTER CASING		SUPPLEMENTARY WELL HISTORY U. S. 600	
NOTICE OF INTENTION TO ABANDON WELL		1	
(INDICATE A POVE BY CUECK		URE OF REPORT, NOTICE, OR OTHER DATA)	·
(INDICATE ABOVE BY CHECK I	MARK NAI	UNE OF REPORT, NOTICE, OR OTHER DATA)	
		America 25, 1999	Q
s wayon redered wan		·	/
HAT. 4 1.1 . 1 464 6.6		Night a second of (E) is a	
is located it. i	rom	line and ft. from him line of sec.	B
84/4 85/4 Sec. 22 1235)		E PA	
(½ Sec. and Sec. No.) (Twp.)	(Ran	ge) (Meridian)	
Lengtio-Settiz (indexignated)	<u> </u>	Ser Aurice	
(Field) (Con	unty or Su	odivision) (State or Territory)	
e elevation of the derrick floor above see	امتحا	;. 12 55.7 ft	
ic elevation of the defiler hoof above see	TICACI		
DE	TAILS	OF WORK	
ate names of and expected depths to objective sands; sho	w sizes, w	OF WORK	men!
ate names of and expected depths to objective sands; sho	w sizes, w	OF WORK	men
ate names of and expected depths to objective sands; sho ing points, and	ow sizes, w I all other	OF WORK eights, and lengths of proposed casings; indicate mudding jobs, co	•men(
ate names of and expected depths to objective sands; sho ing points, and	ow sizes, wi all other	OF WORK eights, and lengths of proposed casings; indicate mudding jobs, co important proposed work) Lgs Cos) to test Pairwage sand at	•m en (
ite names of and expected depths to objective sands; sho ing points, and	ow sizes, wi all other	OF WORK eights, and lengths of proposed casings; indicate mudding jobs, co important proposed work) Lgs Cos) to test Pairwage sand at	•m en (
nte names of and expected depths to objective sands; sho ing points, and intend to drill w/retary tooks ()	ow sizes, will all other	OF WORK eights, and lengths of proposed casings; indicate mudding jobs, co- important proposed work) 25 (20) to test Persyane sand at follows:	men
nte names of and expected depths to objective sands; sho ing points, and intends to drill w/retary tooks ()	ow sizes, will all other	OF WORK eights, and lengths of proposed casings; indicate mudding jobs, co- important proposed work) 25 (20) to test Persyane sand at follows:	·m e n(
nterns to drill w/retary teels () percentage of NO of NO-3/A* 327 ong	w sizes, w i all other	OF WORK sights, and lengths of proposed casings; indicate mudding jobs, comportant proposed work) Iga Co.) to test Fermuse sand at follows:	em en
nterns to drill w/retary teels () percentage of NO of NO-3/A* 327 ong	w sizes, w i all other	OF WORK eights, and lengths of proposed casings; indicate mudding jobs, co- important proposed work) 25 (20) to test Persyane sand at follows:	•m •n (
nte names of and expected depths to objective sands; sho ing points, and extensi to drill w/retary tooks () percentage depth of 3750°, control 111 sec 500° of 10-5/4" 327 ong	w sizes, w i all other	OF WORK sights, and lengths of proposed casings; indicate mudding jobs, comportant proposed work) Iga Co.) to test Fermuse sand at follows:	•m en (
nte names of and expected depths to objective sands; sho ing points, and extensi to drill w/retary tooks () percentage depth of 3750°, control 111 sec 500° of 10-5/4" 327 ong	w sizes, w i all other	OF WORK sights, and lengths of proposed casings; indicate mudding jobs, comportant proposed work) Iga Co.) to test Fermuse sand at follows:	m e n(
nte names of and expected depths to objective sands; sho ing points, and extensi to drill w/retary tooks () percentage depth of 3750°, control 111 sec 500° of 10-5/4" 327 ong	w sizes, w i all other	OF WORK sights, and lengths of proposed casings; indicate mudding jobs, comportant proposed work) Iga Co.) to test Fermuse sand at follows:	men(
nte names of and expected depths to objective sands; sho ing points, and extensi to drill w/retary tooks () percentage depth of 3750°, control 111 sec 500° of 10-5/4" 327 ong	w sizes, w i all other	OF WORK sights, and lengths of proposed casings; indicate mudding jobs, comportant proposed work) Iga Co.) to test Fermuse sand at follows:	m e n (
nte names of and expected depths to objective sands; sho ing points, and extensi to drill w/retary tooks () percentage depth of 3750°, control 111 sec 500° of 10-5/4" 327 ong	w sizes, w i all other	OF WORK sights, and lengths of proposed casings; indicate mudding jobs, comportant proposed work) Iga Co.) to test Fermuse sand at follows:	m e n(
stend to drill w/retary teeks () percentage depth of 3790°, costs 111 set 500° of 10-5/4° 325° ong 111 run and set 145 5-1/3° to 13	to be	OF WORK sights, and lengths of proposed casings; indicate mudding jobs, comportant proposed work) Iga Co.) to test Fermuse sand at follows:	
its names of and expected depths to objective sands; sho ing points, and stems to drill w/retery tools () pureasingle depth of 3790°, conically set 500° of 10-3/4° 325° ong ill run and set 145° 5-1/3° to Till run and set 145° 5-1/3° to Till understand that this plan of work must receive approximate names of and service approximate names of and service approximate names of and expected approximate names of an expected approximate names of a expected approximate names of a expected approximate names of a expected names of a expected approximate names of a expected name	to be	OF WORK eights, and lengths of proposed casings; indicate mudding jobs, co- important proposed work) Age Co.) to test Persone sand at follows: circulated w/1/5 m:	
nterns to drill w/retary tooks (to means to	to be	of Work eights, and lengths of proposed casings; indicate mudding jobs, co important proposed work) Age Coe) to test Ferrome send at follows: circulated w/175 m: carriaging by the Geological Survey before operations may be commence	
nterns to drill w/retary tooks (to means to	to be	of Work eights, and lengths of proposed casings; indicate mudding jobs, co important proposed work) Age Coe) to test Ferrome send at follows: circulated w/175 m: carriaging by the Geological Survey before operations may be commence	
its names of and expected depths to objective sands; sho ing points, and stands to drill w/retary tooks (in parentiments depth of 7750', comis ill set 50' of 10-5/4" 32' ong ill run and set 14' 5-1/3" to Till objective approximated that this plan of work must receive approximately with the fill.	to be	of Work eights, and lengths of proposed casings; indicate mudding jobs, co important proposed work) Age Coe) to test Ferrome send at follows: circulated w/175 m: carriaging by the Geological Survey before operations may be commence	