

NEW MEXICO OIL CONSERVATION COMMISSION
Santa Fe, New Mexico

MISCELLANEOUS NOTICES

Submit this notice in TRIPLICATE to the District Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL		NOTICE OF INTENTION TO DRILL DEEPER	
NOTICE OF INTENTION TO PLUG WELL	X	NOTICE OF INTENTION TO PLUG BACK		NOTICE OF INTENTION TO SET LINER	
NOTICE OF INTENTION TO SQUEEZE		NOTICE OF INTENTION TO ACIDIZE		NOTICE OF INTENTION TO SHOOT (Nitro)	
NOTICE OF INTENTION TO GUN PERFORATE		NOTICE OF INTENTION (OTHER)		NOTICE OF INTENTION (OTHER)	

OIL CONSERVATION COMMISSION
SANTA FE, NEW MEXICO

Hobbs, New Mexico
(Place)

January 16, 1953
(Date)

Gentlemen:

Following is a Notice of Intention to do certain work as described below at the.....

M. O. Rife Jr., et al Elma May Hunt Well No. 1 in
(Company or Operator) (Unit)
SE 1/4 SW 1/4 of Sec. 26, T. 23S, R. 37E, NMPM., Teague Pool
(40-acre Subdivision)
Lea County.

FULL DETAILS OF PROPOSED PLAN OF WORK
(FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

This test has been drilled to total depth of 3585' and appears to be a dry hole. We therefore propose to plug and abandon it at the present depth.

A string of 8-5/8" casing was cemented at depth of 298'. The balance of hole, which is 7-7/8" in diameter, is open. Hole is presently filled with a salt base mud showing viscosity of 37 and water loss of 20. Top of Rustler Anhydrite was encountered at 1110 and the base of salt was reached at 2410'.

We propose to leave hole full of the above described mud and set a tensack cement plug from 2440' to 2410'; a ten sack cement plug from 1140' to 1110'; a ten sack cement plug in bottom of surface casing at 298' then set a regulation marker in cement in the top of surface casing. We will then clear the location site and leave in an orderly condition.

Approved....., 19.....
Except as follows:

M. O. Rife Jr., et al
By Charles P. Miller
Company or Operator

Position..... Agent.....
Send Communications regarding well to:

Approved
OIL CONSERVATION COMMISSION
By Roy Garbrough
Title.....

Name..... M. O. Rife Jr......
Address..... Ft. Worth, Texas......