

NEW MEXICO OIL CONSERVATION COMMISSION

SANTA FE, NEW MEXICO

MISCELLANEOUS NOTICES

Submit this notice in triplicate to the Oil Conservation Commission or its proper agent before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of notice by checking below:

NOTICE OF INTENTION TO TEST CASING SHUT-OFF		NOTICE OF INTENTION TO SHOOT OR CHEMICALLY TREAT WELL	
NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO PULL OR OTHERWISE ALTER CASING	
NOTICE OF INTENTION TO REPAIR WELL		NOTICE OF INTENTION TO PLUG WELL	X
NOTICE OF INTENTION TO DEEPEN WELL			

Hobbs, New Mexico

December 4, 1950

Place

Date

OIL CONSERVATION COMMISSION,
Santa Fe, New Mexico.

Gentlemen:

Following is a notice of intention to do certain work as described below at the

Gulf Oil Corporation Elma Hunt Well No. 1 in SW SE
Company or Operator Lease
of Sec. 26, T. 23S, R. 37E, N. M. P. M., Wildcat Field.
Lea County.

FULL DETAILS OF PROPOSED PLAN OF WORK

FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS OF THE COMMISSION

15 1/2" hole from surface to 304'
13 3/8" OD 48# casing set at 302' - cemented to surface with 500 sacks cement
12 1/4" hole from 304' to 812'
10 3/4" 40# casing set at 812' - not cemented
10" hole from 812' to 1211'
8 5/8" casing set at 1211' - not cemented
8" hole from 1211' to 3401'
6 1/4" hole from 3401' to 3718' - total depth
Rustler formation from 1120' to 1300'
Salt from 1330' to 2510'
Knight section from 3488' to 3580'
Penrose section from 3665' to 3718'

See attached sheet for plugging procedure.

Approved DEC - 5 1950, 19____
except as follows:

Gulf Oil Corporation
Company or Operator

By CHAS. TAYLOR

Position Area Superintendent
Send communications regarding well to

Name Gulf Oil CorporationAddress Box 1667Hobbs, New Mexico

OIL CONSERVATION COMMISSION,
By ROY GUERRERO
Title Oil & Gas Inspector

GULF - ELMA HUNT NO. 1

Plugging Procedure

1. Fill hole full of mud.
2. Plug back from 3718' to 3450' with cement -
6 1/4" hole.
3. Place Calseal plug from 1270 to 1245' - 8" hole
4. Let Calseal set. Plug back from 1245' to 1220'
with cement. 8" hole.
5. Pull 8 5/8" and 10 3/4" casing.
6. Place bridge 25' down inside 13 3/8" casing.
7. Fill top 25' of 13 3/8" casing with cement.
8. Surface cement plug
9. Place 4" pipe marker inside 13 3/8" casing and
extending 4' above mean ground level.

65 sax cement

8 sax Calseal

8 sax cement

20 sax cement

7 sax cement

Totals

100 sax cement

8 sax Calseal

DEC -5 1950

Oil & Gas Inspector



