

NUMBER COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
TRANSPORTER	OIL GAS
PRODUCTION OFFICE	
OPERATOR	

(Form C-102)
(Revised 7/1/62)

NEW MEXICO OIL CONSERVATION COMMISSION
Santa Fe, New Mexico

MISCELLANEOUS NOTICES

strict Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the school on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL		NOTICE OF INTENTION TO DRILL DEEPER	
NOTICE OF INTENTION TO PLUG WELL	X	NOTICE OF INTENTION TO PLUG BACK		NOTICE OF INTENTION TO SET LINER	
NOTICE OF INTENTION TO SQUEEZE		NOTICE OF INTENTION TO ACIDIZE		NOTICE OF INTENTION TO SHOOT (Nitro)	
NOTICE OF INTENTION TO GUN PERFORATE		NOTICE OF INTENTION (OTHER)		NOTICE OF INTENTION (OTHER)	

OIL CONSERVATION COMMISSION
SANTA FE, NEW MEXICO

Roswell, New Mexico
(Place)

February 25, 1963
(Date)

Gentlemen:

Following is a Notice of Intention to do certain work as described below at the

The Atlantic Refining Company, Melba Gains, Well No. 1 in P
(Company or Operator) Lease (Unit)
SE 1/4 SE 1/4 of Sec. 27, T. 23-S, R. 37-E NMPM, Teague Pool
(40-acre Subdivision)
Lea County.

FULL DETAILS OF PROPOSED PLAN OF WORK
(FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

This well is presently completed in McKee zone perms from 9389'-9420'. The McKee zone was non-commercial and no allowable was obtained for it. We propose to plug and abandon this well in the following manner:

1. 25 sk. cement plug from 9440'-9250'.
2. Shoot off and pull 5 1/2" casing from approximately 4800'.
3. 25 sk. cement plug - 1/2 in and 1/2 out of 5 1/2" stub.
4. 25 sk. cement plug from 3430'-3350' (Queens).
5. 30 sx from 2940'-2860' (bottom of 8-5/8" intermediate casing @ 2899.96').
6. 10 sk. cement plug in top of 8-5/8" casing.

Intermediate and surface casing strings will remain intact. 9# mud will be used to spot cement plugs.

Approved....., 19.....
Except as follows:

Approved
OIL CONSERVATION COMMISSION

By.....
Title.....

The Atlantic Refining Company
Company or Operator

By.....
Position..... District Drilling Supervisor
Send Communications regarding well to:

Name..... The Atlantic Refining Company
Address..... P.O. Box 1978, Roswell, New Mexico