

## NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

## MISCELLANEOUS NOTICES

HOBBBS OFFICE O. C. C.

JUN 16 10 44 AM '64

Submit this notice in TRIPLICATE to the District Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL		NOTICE OF INTENTION TO DRILL DEEPER	
NOTICE OF INTENTION TO PLUG WELL	X	NOTICE OF INTENTION TO PLUG BACK		NOTICE OF INTENTION TO SET LINER	
NOTICE OF INTENTION TO SQUEEZE		NOTICE OF INTENTION TO ACIDIZE		NOTICE OF INTENTION TO SHOOT (Nitro)	
NOTICE OF INTENTION TO GUN PERFORATE		NOTICE OF INTENTION (OTHER)		NOTICE OF INTENTION (OTHER)	

OIL CONSERVATION COMMISSION  
SANTA FE, NEW MEXICO

Kermit, Texas

(Place)

June 15, 1964

(Date)

Gentlemen:

Following is a Notice of Intention to do certain work as described below at the

Gulf Oil Corporation

E. C. Hill Tr "B"

Well No. 2 in J

(Company or Operator)

NW 1/4 SE 27 23-8 37-E Teague Ellenburger Pool

(40-acre Subdivision)

Lea

County.

FULL DETAILS OF PROPOSED PLAN OF WORK  
(FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

Subject well was originally completed 4-14-51, at a plug back depth of 9749'. Currently the well has an accumulative oil production of 158,735 bbls. and is producing 100% water.

It is proposed to spot cement plug from 9749' to 9485', mud to 4725', cut 7" csg at approximately 4700' and pull; cement 4725' to 4675'; mud to 3865'; cement 3865' to 3815' (Top Judkins pay 3840'); mud to 3425'; cement 3425' to 3375' (Top Penrose pay 3400'); mud to 2893'; cement 2893' to 2843' (Shoe of 9 5/8" casing @ 2868); mud to 1425'; cut 9 5/8" csg at approximately 1400' and pull; cement 1425' to 1375'; mud to 1100'; cement 1100' to 1050' (Top Rustler 1075'); mud to 336'; cement 336' to 286' (Shoe 13 3/8" csg @ 311'); mud to 50'; cement to surface; leaving 5079' of 7" casing, 1468' of 9 5/8" casing, and 311' of 13 3/8" casing in hole. Set marker and abandon well leaving location clean.

Approved \_\_\_\_\_, 19\_\_\_\_  
Except as follows:Approved \_\_\_\_\_  
OIL CONSERVATION COMMISSION

By \_\_\_\_\_

Title \_\_\_\_\_

Gulf Oil Corporation

Company or Operator

By \_\_\_\_\_

Area Production Manager

Position \_\_\_\_\_

Send Communications regarding well to:

Name \_\_\_\_\_ Gulf Oil Corporation

Address \_\_\_\_\_ P. O. Box 980, Kermit, Texas