

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

HOODS OFFICE O. C. C.

MISCELLANEOUS NOTICES JUN 22 8 34 AM '64

Submit this notice in TRIPLICATE to the District Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL		NOTICE OF INTENTION TO DRILL DEEPER	
NOTICE OF INTENTION TO PLUG WELL	X	NOTICE OF INTENTION TO PLUG BACK		NOTICE OF INTENTION TO SET LINER	
NOTICE OF INTENTION TO SQUEEZE		NOTICE OF INTENTION TO ACIDIZE		NOTICE OF INTENTION TO SHOOT (Nitro)	
NOTICE OF INTENTION TO GUN PERFORATE		NOTICE OF INTENTION (OTHER)		NOTICE OF INTENTION (OTHER)	

OIL CONSERVATION COMMISSION
SANTA FE, NEW MEXICO

Kermit, Texas

(Place)

June 19, 1964

(Date)

Gentlemen:

Following is a Notice of Intention to do certain work as described below at the Gulf Oil Corporation

E. C. Hill Tr. "A"

Well No. 4 in N

SE SW (Company or Operator) 21 T. 23S 37E Lease Teague McKee (Unit)
(40-acre Subdivision) 1/4 of Sec. NMPM, Pool
Lea County.

FULL DETAILS OF PROPOSED PLAN OF WORK

(FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

Subject well was originally completed 2-1-53 in the Teague Ellenburger pay with a plug back depth of 9743'. In 7-6-57 the well was plugged back to the Teague McKee pay by squeezing Ellenburger perforation with 78 sacks of cement. Max. pressure 4000#. Top of plug 9490'. The Teague McKee was uneconomical to produce and was temporarily abandoned 3-24-59.

It is proposed to spot 25 sacks cement @ 9100' (Top of McKee pay); mud to 5200'; cut 5½" casing at approximately 5200' and pull; cement plug 25 sacks @ 5200'; mud to 4918'; cement plug 25 sacks @ 4918' (Top of Glorieta pay 4918'); mud to 3920'; cement plug 25 sacks @ 3920' (Top of Judkins @ 3920'); mud to 3365'; cement plug 25 sacks @ 3365' (Top of Penrose @ 3365'); mud to 2899'; cement plug 25 sacks @ 2899' (shoe of 8 5/8" casing; mud to 50'; cement plug 50' to surface; leaving 4542' of 5½" casing; 2899' of 8 5/8" casing and 320' of 13 3/8" casing in the hole. Set marker and abandon well leaving location clean.

Approved....., 19.....
Except as follows:

Approved
OIL CONSERVATION COMMISSION

By.....
Title.....

Gulf Oil Corporation
Company or Operator

By.....
Position..... Area Production Manager
Send Communications regarding well to:

Name..... Gulf Oil Corporation
Address..... P. O. Box 980, Kermit, Texas