

NEW MEXICO OIL CONSERVATION COMMISSION
Santa Fe, New Mexico

MISCELLANEOUS NOTICES

Submit this notice in TRIPPLICATE to the District Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL		NOTICE OF INTENTION TO DRILL DEEPER	
NOTICE OF INTENTION TO PLUG WELL		NOTICE OF INTENTION TO PLUG BACK		NOTICE OF INTENTION TO SET LINER	
NOTICE OF INTENTION TO SQUEEZE	<input checked="" type="checkbox"/>	NOTICE OF INTENTION TO ACIDIZE		NOTICE OF INTENTION TO SHOOT (Nitro)	
NOTICE OF INTENTION TO GUN PERFORATE	<input checked="" type="checkbox"/>	NOTICE OF INTENTION (OTHER) Fracture treat	<input checked="" type="checkbox"/>	NOTICE OF INTENTION (OTHER)	

OIL CONSERVATION COMMISSION
SANTA FE, NEW MEXICO

Hobbs, New Mexico
(Place)

July 2, 1957
(Date)

Gentlemen:

Following is a Notice of Intention to do certain work as described below at the.....

Gulf Oil Corporation E. C. Hill (Tr. A) Well No. 4 in N
(Company or Operator) (Lease) (Unit)
SE 1/4 SW 1/4 of Sec. 27, T. 23-S, R. 37-E, NMPM., Teague Ellenburger Pool
(40-acre Subdivision)
Lea County.

FULL DETAILS OF PROPOSED PLAN OF WORK

(FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

It is proposed to abandon Teague Ellenburger and recompleat as Teague as follows:

1. Pull 2-3/8" tubing and Kobe pump. Run 2-3/8" tubing with Baker seal nipple and set in Baker Model "D" packer. Squeeze perforations below packer(9733-9660').
2. Pull 2-3/8" tubing. Run Gamma Ray Neutron survey. Set production packer on wire line in interval of 9100-9125'. Run 2-3/8" tubing with Baker seal assembly, with circulating valve above seal nipple.
3. Perforate 5-1/2" casing as determined by Gamma Ray Neutron survey. Swab and Test. If warranted acidize with 500 gallons mud acid. Treat formation thru perforations in casing with 10,000 gallons gelled lease oil with 1# sand per gallon.

Approved....., 19.....
Except as follows:

Approved
OIL CONSERVATION COMMISSION

By.....
Title.....

Gulf Oil Corporation
Company or Operator

By E. F. Taylor

Position Area Supt. of Prod.
Send Communications regarding well to:

Name Gulf Oil Corporation

Address Box 2167, Hobbs, New Mexico