Form 9-331 (May 1903) UNIT STATES SUBMIT IN TRIPLAC (Other Instructions) DEPARTMENT OF THE INTERIOR verse side) DEPARTMENT OF THE INTERIOR verse side) Of the instructions of the instruction of the instructio	Porth Approved, Budget Bureau No. 42 R1424. 6. 5, LEANE DESIGNATION AND REFIAL NO.	
GEOLOGICAL SURVEY	LC-030187	
SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT-" for such proposals)	G. IF INDIAN, ALLOTTEE OR TRIBE NAME	
	7. UNIT AUREEMENT NAME	
2. NAME OF OPERATOR	8. FARM OR LEASE NAME	
Gulf Oil Corporation U.S. Crow	C. E. LaMunyon	
	9 WELL NO	
Box 670, Hobbs, New Mexico 88240	19	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.)	10. FIELD AND POOL, OR WILDCAT	
At surface	Langlie Mattix 11. SEC. T., R., M., OR BLK. AND	
	NURVEY OR AREA	
1980' FNL & 660' FEL, Section 27, 23-S, 37-E		
14. PERMIT NO. 15. ELEVATIONS (Show whether DF, RT, GR, etc.)	Sec 27, 23-5, 37-E 12. COUNTY OF PARISH 13. STATE	
3264' GL	Lea New Mexico	
16. Check Appropriate Box To Indicate Nature of Notice, Report,	or Other Data	
NOTICE OF INTENTION TO: 80	BSEQUENT REPORT OF:	
TEST WATER SHUT-OFF PULL OR ALTER CASING WATER SHUT-OFF	REPAIRING WELL	
FRACTURE TREAT MULTIPLE COMPLETE FRACTURE TREATMENT	ALTERING CASING	
SHOOT OR ACIDIZE ABANDON* SHOOTING OR ACIDIZING	ABANDON MENT [•] XX	
REPAIR WELL CHANGE PLANS (Other)		
(Other)	(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)	
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent of proposed work. If well is directionally drilled, give subsurface locations and measured and true with nent to this work.) *	dates, including estimated date of starting any vertical depths for all markers and zones perti-	
TO 3580		
3577' PB.		

Set CI BP at 3425'. Loaded casing with 9.3# abandonment mud. Spotted 35 sack Class C cement plug from 3425' to 3200', abandoning perforations 3478' to 3564'; 25 sack Class C plug from 2650' to 2500'; 25 sack Class C plug from 1250' to 1100'; 25 sack Class C plug from 410' to 260', across 9-5/8" shoe at 335' and 10 sack Class C plug from 50' to surface. Installed dry hole marker and cleaned location. Plugged and abandoned February 5, 1976. Location is ready for your final inspection.

18. I hereby certify that the foregoing is true and cor SIGNED D. T. Berlin	rectArea_Engineer	February 5, 1976
(This space for Federal or State office use)		
APPROVED BY CONDITIONS OF APPROVAL, IF ANY :	TITLE	APPROVED
	*See Instructions on Reverse Side	JUN 2 1976 BERNARD MOROZ

.