

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or deepen or reentry to a different reservoir.

Use "APPLICATION FOR PERMIT-" for such proposals

SUBMIT IN TRIPLICATE

1. Type of well

☒ Oil ☐ Gas ☐ Other

2. Name of Operator

CHEVRON U.S.A. INC.

3. Address and Telephone No.

P.O. BOX 1150 MIDLAND, TEXAS 79702 ATTN: P.R. MATTHEWS, ROOM 4115-A

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

SEC. 27, T23S, R37E

660 FWL & 1980' FNL

UNIT E

5. Lease Designation and Serial No.

LC-630187

6. If Indian, Allottee or Tribe Name

N/A

7. If Unit or CA, Agreement Designation

N/A

8. Well Name and No.

C.E. LA MUNYON FED (*C) #1

9. API Well No.

30-025-10860

10. Field and Pool, or Exploratory Area

LANGLIE MATTIX SRQNB

11. County or Parish, State

LEA COUNTY, NEW MEXICO

CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

12 TYPE OF SUBMISSION

☒ Notice of Intent

☐ Subsequent Report

☐ Final Abandonment Notice

TYPE OF ACTION

☐ Abandonment

☐ Recompletion

☐ Plugging Back

☐ Casing Repair

☐ Altering Casing

☒ Other

P & A

☐ Change of Plans

☐ New Construction

☐ Non-Routine Fracturing

☐ Water Shut-Off

☐ Conversion to Injection

☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimate date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

IT IS PROPOSED TO: PLUG & ABANDON WELL

TIH AND TAG CIBP AT 3440', LOAD HOLE W/FW & TEST TO 300#. SPOT 200' OF CMT F/3440-3240.

ABOVE PLUG WILL COVER QUEEN, PENROSE & GRAYBURG.

SPOT 530' CMT F/2870'-2340', COVERS YATES & 7-RIVERS.

PERF AT 1200', TIH & SET CIGR AT 1000', SQZ W/ 85 SXS. CMT. PULL OUT, LEAVE 35' CMT ON TOP.

ABOVE PLUG COVERS TOP OF SALT AND RUSTLER.

SPT 250' F/450'-200', COVERS 10.75" CSG. SHOE. SPOT 100' PLUG F/SURFACE TO 100'.

10# P & A MUD WILL BE PLACED BETWEEN ALL CEMENT PLUGS.

CUT OFF WELLHEAD AND INSTALL P & A MARKER.

CHANGE WELL STATUS TO P & A.

14. I hereby certify that the foregoing is true and correct

Signed *P.R. Matthews*

Title

TECHNICAL ASSISTANT

Date

5/12/92

(This space for Federal or State official use)

Approved by *[Signature]*

Title

Date

5-15-92

Conditions of approval, if any:

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

*See Instructions on Reverse Side

RECEIVED

MAY 19 1992

OCD HOBBS OFFICE