

U.S. G.S. FORM 100-1
MAY 1969 EDITIONUNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPPLICATE
(Other instructions on reverse side)Form approved.
Budget Bureau No. 42-R1424.
5. LEASE DESIGNATION AND SERIAL NO.

LC-030187

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Use not on this form for proposals to drill or to deepen or plug back a well. Use "APPLICATION FOR PERMIT" for such proposals.)

RECEIVED

FEB 5 1981

1. NAME OF OPERATOR

2. NAME OF OPERATOR

Gulf Oil Corporation

3. ADDRESS OF OPERATOR

P. O. Box 670, Hobbs, NM 88240

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.)

5. SURFACE

660' FNL & 990' FEL

12. SURFACE NO.

13. ELEVATIONS (Show whether DF, RT, GR, etc.)

3251' GL

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Lamunyon Federal "C"

9. WELL NO.

2

10. FIELD AND POOL, OR WILDCAT

Jalmat

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec 27-T23S-R37E

12. COUNTY OR PARISH

Lea

13. STATE

NM

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NATURE OF INTENTION TO:

1. TEST WATER OR LOG

2. DRILL OR ALTER CASING

3. FRACTURE TREAT

4. MULTIPLE COMPLETE

5. SHOOT OR ACIDIZE

6. ABANDON*

7. PLUG OR WELL

8. CHASE PLANS

9. OTHER P&A

SUBSEQUENT REPORT OF:

10. WATER SHUT-OFF

11. REPAIRING WELL

12. FRACTURE TREATMENT

13. ALTERING CASING

14. SHOOTING OR ACIDIZING

15. ABANDONMENT*

(Other)

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

16. * If well is to be abandoned, clearly state all pertinent details, and give pertinent dates, including estimated date of starting any plug back, if well is successfully drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.

POH with production equipment. Set cement retainer at 2550'. Squeeze perfs with 75 sacks Class "C" neat mixed to 14.8#/gal. Perf at 1050' with (2) 1/2" JHPF. Set cement retainer at 1000'. Squeeze perfs with 75 sacks Class "C" neat mixed to 14.8#/gal. Spot excess cement on retainer. Circulate abandonment mud back to surf. Spot 10 sack surface plug. Place dry hole marker. Clear and clean location.

17. I hereby certify that the foregoing is true and correct

8. SIGNATURE

R. D. White

9. TITLE

Area Engineer

10. DATE

2-2-81

11. This space for Federal or State Approval

(Orig Sgd.) PETER W. CHESTER

12. APPROVED BY

13. TITLE

14. DATE

15. CONDITIONS OF APPROVAL, IF ANY:

MAR 18 1981

JAMES A. GILLHAM
DISTRICT SUPERVISOR

See Instructions on Reverse Side