

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRI
(Other instruction
verne slide)

ATE
n re

Form approved.
Budget Bureau No. 1004-0135
Expires August 31, 1985

5. LEASE DESIGNATION AND SERIAL NO.

LC 030187

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT-" for such proposals.)

1.

OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR

John H. Hendrix Corporation

3. ADDRESS OF OPERATOR

223 W. Wall, Suite 525, Midland, TX 79701

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.
See also space 17 below.)
At surface

1980' FNL & 660' FEL, Sec. 29, T23S, R37E,
Lea County, NM Unit #

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

12. COUNTY OR PARISH

Lea

13. STATE

NM

10.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETION

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

6/19/91 RIH w/ tbg. to 3557' & tagged fill.

6/20/91 Pulled tbg. to 3481' & displaced hole w/ gelled water & spotted 25 sx. plug at 3481'. Pulled 15 stands & waited 4 hrs. Ran tbg. & tagged cement at 3146'. Pulled tbg. to 1163' & spotted 25 sx. plug. Top of cement at 828'. Pulled 11 jts. 4-1/2" csg. Ran tbg. to 355'. Circ. cement to surface in 8-5/8" csg. Installed dry hole marker. Top of 4-1/2" is at 329'. Well is now P&A.

Approved by the Director of the Bureau.
Liability under bond is void until
surface restoration is completed.

18. I hereby certify that the foregoing is true and correct

SIGNED

Ramiro H. Westbrook

TITLE

Vice-President

DATE

8/14/91

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

8-19-91

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side