

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

RECEIVED
7-22-84

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐	2. NAME OF OPERATOR John H. Hendrix Corporation	3. ADDRESS OF OPERATOR 223 W. Wall, Suite 525, Midland, TX 79701	4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.) At surface 1980' FNL & 660' FEL, Sec. 29, T23S - R37E, Lea County, NM	5. FIELD AND POOL, OR WELLBORE Lanclio Habbit	6. COUNTY OR PARISH Lea	7. STATE New Mex.
14. PERMIT NO.	15. ELEVATIONS (Show whether OF, AT, OR, etc.)					

10. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT ON:	
TEST WATER SHUT-OFF	☐	WATER SHUT-OFF	☐
FRACUTURE TREAT	☐	FRACUTURE TREATMENT	☐
SHOOT OR ACIDIZE	☐	SHOOTING OR ACIDIZING	☐
REPAIR WELL	☐	(Other)	☐
(Other)	☐	(Other)	☐

(Note: Report results of multiple completion or Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and points pertinent to this work.)

Well has parted 4-1/2" csg. at approximately 335'. Have not been able to get tbg. inside 4-1/2" csg.

Proposed Work

1. Pick up 2-3/8" tbg.
2. Run in hole w/ tbg. bent slightly on bottom and try to get inside 4-1/2" csg. If successful, spot 300' plug at 3500'. (Perfs. 3520' to 3592'). TAG PLUG.
3. Spot 100' plug at 1150' inside 4-1/2" csg. Top of cement behind 4-1/2" csg. is 1100'. TAG PLUG.
4. Set retainer at 250' and circ. cement to surface.
5. 10 sx. at surface.
6. Dry hole marker.
7. ~~If we cannot get inside 4 1/2" csg. w/ bent tubing:~~
 - A. ~~Set retainer at 250' and pump cement until 4 1/2" perfs. squeezed off and cement circulates to surface between 2 5/8" and 4 1/2".~~
 - B. ~~Top plug and dry hole marker.~~

18. I hereby certify that the foregoing is true and correct

SIGNED Forrest H. Washburn TITLE Vice-President DATE April 2, 1984

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE 4-23-84

CONDITIONS OF APPROVAL, IF ANY:

Approved by the Director of the Bureau of Land Management
This report is to be filed with the Bureau of Land Management
and the State of New Mexico.

*See Instructions on Reverse Side