N.M. Oil CONS. COMMISSION P.O. BOX 1980

HOBBS, NEW MEXICO 88240

Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

Form 3160-5 (June 1990)

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FORM APPROVED Budget Bureau No. 1004-0135

		Expires:	March	31, 199)3
5.	Lease	Designat	ion and	Serial	No.

SUNDRY NOTICES Do not use this form for proposals to dr Use "APPLICATION FOR	NMLC030187 6. If Indian, Allottee or Tribe Name		
SUBMIT	7. If Unit or CA, Agreement Designation		
1. Type of Well Solit Gas Other	8. Well Name and No. LaMunyon #2 9. API Well No. 300251086800S1 10. Field and Pool, or Exploratory Area Langlie Mattix 11. County or Parish, State Lea County, NM		
12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPO	RT, OR OTHER DATA	
TYPE OF SUBMISSION			
Notice of Intent Subsequent Report	Abandonment Recompletion Plugging Back Casing Repair	Change of Plans New Construction Non-Routine Fracturing Water Shut-Off	
Final Abandonment Notice	☐ Altering Casing	L_J Conversion to Injection	

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

In response to your letter of February 1, 1994, please be advised that we request approval to temporarily abandon this well. It is being held for waterflood possibilities. We will perform an integrity test within 30 days.

			U	•
14. I hereby certify that the foregoing is true and correct Signed Roomic H. West brook	Title	Vice-President	Date3/23/94	
(This space for Federal or State office use) (ORIG. SGD.) JOE G. LARA Approved by	Title	PETROLEUM ENGINEER	Date 4/1.3/94	/
Conditions of approval, if any: Sec attached				

MINIMUM REQUIREMENTS FOR CASING INTEGRITY TESTING OF WELLS ON FEDERAL LEASES IN THE CARLSBAD RESOURCE AREA

1. Contact the appropriate BLM office at least 24 hours prior to the scheduled test.

NOTE: A BLM tecnician must be present to witness all casing integrity tests.

- 2. A retrievable bridge plug or packer shall be set a maximum of fifty (50) feet above any open perforations.
- 3. All downhole production equipment (tubing, rods, etc.) must be removed from the casing if they are not isolated by a packer.
- 4. The casing must be filled with fluid and pressure tested to 500 PSI. Further, the casing must be capable of holding this pressure for at least 30 minutes with a 10% allowable leak-off (ie., down to 450 PSI).
- 5. Wells that successfully pass the casing integrity test will be approved for Temporary Abandonment status for a period of 12 months provided that the operator submits a subsequent Sundry Notice requesting TA approval, and attaches a copy of The pressure test chart for the tested well.