



UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

C O P Y

Land Office Las Cruces
Lease No. 030187
Unit _____

RECEIVED

AUG 22 1951

SUNDRY NOTICES AND REPORTS ON WELLS

OIL CONSERVATION COMMISSION

NOTICE OF INTENTION TO DRILL.....	<input checked="" type="checkbox"/>	SUBSEQUENT REPORT OF WATER SHUT-OFF.....	<input type="checkbox"/>
NOTICE OF INTENTION TO CHANGE PLANS.....	<input type="checkbox"/>	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.....	<input type="checkbox"/>
NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....	<input type="checkbox"/>	SUBSEQUENT REPORT OF ALTERING CASING.....	<input type="checkbox"/>
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL.....	<input type="checkbox"/>	SUBSEQUENT REPORT OF REDRILLING OR REPAIR.....	<input type="checkbox"/>
NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....	<input type="checkbox"/>	SUBSEQUENT REPORT OF ABANDONMENT.....	<input type="checkbox"/>
NOTICE OF INTENTION TO PULL OR ALTER CASING.....	<input type="checkbox"/>	SUPPLEMENTARY WELL HISTORY.....	<input type="checkbox"/>
NOTICE OF INTENTION TO ABANDON WELL.....	<input type="checkbox"/>		<input type="checkbox"/>

HOBBS OFFICE

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

April 17

19 51 40

LaMunyon

Well No. 2 is located 1980 ft. from N line and 660 ft. from W line of sec. 29
NW/4 Section 29 23S 37E NMPM
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)
South Skelly Lea New Mexico
(Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is 3320 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate muddling jobs, cementing points, and all other important proposed work)

Expected formation tops: Top Anhydrite 1150, Top Salt 1300, Base Salt, 2600,
Producing sand (Knight Series) 3450', Penrose Sand 3570', Total Depth 3625'.
Expected pay from 3500' to TD.

CASING PROGRAM

30' - 13" OD Armco 3-gauge Steel. 40 sacks cement (cement to surface)
1200' - 8 5/8" OD 32# SS casing, 400 sacks cement (cement to surface)
3450' - 6" OD 16# SS casing, 700 sacks common (or equivalent of 4% Aquagel cement)
(to be cemented to bottom of intermediate string)

To be drilled with rotary tools to total depth, using mud as circulating medium to point at which oil string of casing is set, and using oil for circulating medium to that point to total depth. If necessary to shoot cable tools will be used to
I understand that this plan of work must receive approval in writing by the Geological Survey before
operations may be commenced. clean out.

Company Gulf Oil Corporation

Address Box 661

Tulsa, Oklahoma

By /S/ A. N. Bell, Jr.

Title Ass't General Superintendent