

DUPLICATE

COPY FOR
STATE OF NEW MEXICO
OIL CONSERVATION
COMMISSION
SUBMIT IN TRIPLICATE TO
DISTRICT OFFICE

Land Office Las Cruces

Lease No. 030187

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Unit
RECEIVED
AUG 22 1951
OIL CONSERVATION COMMISSION
MOBBS-OFFICE

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL.....	<input checked="" type="checkbox"/>	SUBSEQUENT REPORT OF WATER SHUT-OFF.....	
NOTICE OF INTENTION TO CHANGE PLANS.....		SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.....	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....		SUBSEQUENT REPORT OF ALTERING CASING.....	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL.....		SUBSEQUENT REPORT OF REDRILLING OR REPAIR.....	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....		SUBSEQUENT REPORT OF ABANDONMENT.....	
NOTICE OF INTENTION TO PULL OR ALTER CASING.....		SUPPLEMENTARY WELL HISTORY.....	
NOTICE OF INTENTION TO ABANDON WELL.....			

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

Tulsa, Oklahoma August 26, 1944

LaMunyon

Well No. 4 is located 660 ft. from N line and 660 ft. from W line of sec. 29

NW 1/4 of Sec. 29
(1/4 Sec. and Sec. No.)

23S
(Twp.)

37E
(Range)

NMPM
(Meridian)

South Skelly
(Field)

Lea
(County or Subdivision)

New Mexico
(State or Territory)

The elevation of the derrick floor above sea level is ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate muddling jobs, cementing points, and all other important proposed work)

Expected formation tops: Anhydrite 1150'; Salt 1300'; Base salt 2600'. Producing Sand (Knight Series) 3450'; Penrose Sand 3570'. Total depth 3625'. Expected pay 3500' to total depth.

CASING PROGRAM:

30' of 13" OD Armco 3-gauge steel cemented to surface with 40 sacks.
1200' of 8-5/8" OD 32# SS casing cemented to surface with 400 sacks.
3450' of 5-1/2" OD 14# SS Grade H casing cemented to bottom of intermediate string with 700 sacks common cement (or equivalent of 4% Aquagel cement).
Well will be drilled with rotary tools to the top of the Knight series, or to the approximate depth of 3450', at which point oil string of casing will be cemented; and I understand that this plan of work must receive approval in writing by the Geological Survey before mud will be used as circulating medium. After oil string is set, the well will be standardized, deepened to approximately 3625', shot if necessary, and completed with cable tools.
Company Gulf Oil Corporation

Address P. O. Box 661

Tulsa 2, Oklahoma

By S/ A. N. Bell Jr.

Title Asst General Superintendent