Form 3160-5 (November 1994)

## UNI J STATES DEPARTMENT OF THE INTERIOR **BUREAU OF LAND MANAGEMENT**

N.M.	Ji.	ons. Div	ISION APPROVED OMB No. 1004-013
1625	N.	French Dr	Expures July 31, 199

1625 N. Fre	nch Dr. Expure	no 1004-0135 s July 31, 1996
Hobbs, NM	8874 Gnal No 8970138170	- 4057420

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to re-enter an 6. If Indian, Allottee or Tribe Name abandoned well. Use Form 3160-3 (APD) for such proposals. 7. If Unit or CA/Agreement, Name and/or No. SUBMIT IN TRIPLICATE - Other instructions on reverse side MYERS LANGLIE MATTIX UNIT Type of Well 11007 Well Name and No. Oil Well Gas Well & Other Thierich 45 2. Name of Operator OXY USA Inc. 16696 9. API Well No.

30-025-10876 P.O. BOX 50250 3b. Phone No. (include area code) 3a. Address MIDLAND, TX 79710-0250 915-685-5717 10. Field and Pool, or Exploratory Area Location of Well (Footage, Sec., T., R., M., or Survey Description) LANGLIE MATTIX 7 RVRS Q-G 11. County or Parish, State

660 FSL 1980 FEL SUSE(0) Sec 29 T235 R37E

LEA NM

12. CHECK APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION		TY	PE OF ACTION	
Nouce of Intent  Subsequent Report  Final Abandonment Nouce	Acidize Alter Casing Casing Repair Change Plans Convert to Injection	Deepen Fracture Treat New Construction Plug and Abandon Plug Back	Production (Start/Resume) Reclamation Recomplete Temporarily Abandon Water Disposal	Water Shut-Off Well integrity Other

13. Describe Proposed or Completed Operation (clearly state all pertinent details, including estimated starting date of any proposed work and approximate duration thereof. If the proposal is to deepen directionally or recomplete horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones. Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports shall be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompletion in a new interval, a Form 3160-4 shall be filed once testing has been completed. Final Abandonment Notices shall be filed only after all requirements, including reclamation, have been completed, and the operator has determined that the site is ready for final inspection.)

MLMU #45 - INJECTION-BLM

TD-3625' PERFS-3382-3607' CONDITIONS OF APPROVAL

10-3/4" 40# CSG @ 304' W/ 150sx, 13-3/4" HOLE, TOC-CIRC 7" 20# CSG @ 3403' W/ 100sx, 8-3/4" HOLE, TOC-2738'-CALC

1. 6/51-PERF @ 1200', SQZ W/ 150sx, WOC, TOC-259'-CALC

2. 6/51-SQZ PERF @ 1200 W/ 100sx

4-1/2" 11.6# CSG @ 3098-3624' W/ 500sx, 6-1/2" HOLE, TOC-3098'-CIRC

- RIH & SET CIBP @ 3332', M&P 30sx CMT TO 3054'
- PERF @ 2850', SQZ W/ 40sx TO 2750', WOC & TAG
- M&P 25sx @ 1250-1150'
- RIH & SET CR @ 300', SQZ CSG LK @ 325-421' W/ 75sx CMT TO 254', WOC & TAG
- M&P 10sx CMT SURFACE PLUG
- 10# MLF BETWEEN PLUGS

14. I hereby certify that the foregoing is true and correct Name (Printed/Typed)	Title
DAVID STEWART	REGULATORY ANALYST
Signature Sem - Stell	Date (1/21/00

THIS SPACE FOR FEDERAL OR STATE OFFICE USE PETROLEUM ENGINEER" (ORIG. SGD.) ALEXIS C. SWOBODA NOV 22 2000 Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, ficutious or fraudulent statements or representations as to any matter within its jurisdiction.

OXY USA INC. PROPOSED MYERS LANGLIE MATTIX UT 45 SEC 29 T23S R37E LEA NM

0.0 - 65.0' CEMENT PLUG 10sx

300.0 - 300.0' RETAINER 254.0 - 421.0' CEMENT PLUG 75sx 0.0 - 304.0' 13 3/4" OD HOLE 0.0 - 304.0' CEMENT 150sx 0.0 - 304.0' 10 3/4" OD SURF CSG

325.0 - 421.0' SQUEEZE PERFS CSG LK

1150.0 - 1250.0' CEMENT PLUG 25sx 259.0 - 1200.0' CEMENT 150sx-CALC-6/51 1200.0 - 1200.0' CEMENT 100sx-6/51

1200.0 - 1200.0' SQUEEZE PERFS 6/51

304.0 - 3403.0' 8 3/4" OD HOLE 2738.0 - 3403.0' CEMENT 100sx-CALC 0.0 - 3403.0' 7" OD PROD CSG

2705.0 - 2805.0' CEMENT PLUG 40sx

3054.0 - 3332.0' CEMENT PLUG 30sx 3332.0 - 3332.0' CIBP 3403.0 - 3625.0' 6 1/4" OD HOLE 3098.0 - 3624.0' CEMENT 500sx 3098.0 - 3624.0' 4 1/2" OD LINER 3382.0 - 3607.0' ABANDONED PERFS

TD: 3625'