

Form 9-331
Dec. 19735-USGS-HOBBS ✓
1-R.J. STARRAK-TOLSA
1-A.B. CARY-MIDLAND
UNITED STATES1-ELB, ENGR.
1-HCL, FOREMAN
10-WIO's
1-BH, FIELD CLERKForm Approved.
Budget Bureau No. 42-R1424DEPARTMENT OF THE INTERIOR-FILE
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☒ gas ☐
well well other2. NAME OF OPERATOR
Getty Oil Company3. ADDRESS OF OPERATOR
P. O. Box 730, Hobbs, New Mexico 882404. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: Unit 1tr. P, 990' FSL & 990' FEL
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐☐
☐
☐
☐
☐
☐
☐
☐

(other) Return to production X

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Cleaned out to TD 3650'. Western Co. ran GRN Log 3650-3300'. Set 119 jts. (3634') 2 3/8" OD tubing at 36483'. Ran 2" x 1 1/4" x 12' RWTC pump and 143 (3575') 3/4" rods. Placed well pumping on 6-22-77.

RECEIVED
DEC 12 1978U. S. GEOLOGICAL SURVEY
HOBBS, NEW MEXICO

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED DALE R. CROCKETT TITLE AREA SUPT. DATE 12-11-78

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY: