

NO. OF COPIES RECEIVED	
DISTRIBUTION	
LAND OFFICE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

042 — P.O. BOX 1980
HOBBS, N.M. 88240 (LEA COUNTY)

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease
State ☐ Fee ☒

5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS

DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO RE-ENTER OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT TO DRILL OR TO RE-ENTER OR PLUG BACK TO A DIFFERENT RESERVOIR."

1. ☐ OIL WELL ☐ GAS WELL ☐ OTHER- Plugged & abandoned well

2. Name of Operator
Getty Oil Company

3. Address of Operator
P. O. Box 730, Hobbs, New Mexico 88240

4. Location of Well
UNIT LETTER N 1980 FEET FROM THE West LINE AND 660 FEET FROM
THE South LINE, SECTION 30 TOWNSHIP 23S RANGE 37E N.M.P.M.

7. Unit Agreement Name

8. Farm or Lease Name

Cowden

9. Well No.

41

10. Field and Pool, or Wildcat

15. Elevation (Show whether DF, RT, GR, etc.)

12. County

Lea

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐
TEMPORARILY ABANDON ☐
PULL OR ALTER CASING ☐

PLUG AND ABANDON ☐

CHANGE PLANS ☐

OTHER Reenter and replug ☒

1-R.J. STARRAK-TULSA
1-A.B. CARY-MIDLAND
* 1-E. Buttriss, ENGINEER
c 1-H.C. Little, FOREMAN - MLMU
c 1-FILE
O- WIO's -LIST ATTACHED
1-BH, FIELD CLERK

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

According to the NMOCC Order No. 460 for the expansion of our Myers Langlie Mattix Unit, this well must be properly plugged before water can be injected within a 1/2 mile radius. We plan to reenter and replug the well using the following procedure:

1. Rig up pulling unit and install BOP.
2. Drill out cement plug 1185-1208'.
3. Go to 5 1/2" casing cutoff at 3000'.
4. Displace hole with 10# mud.
5. Spot 30 sxs. cement plug 2950-3050' over 5 1/2" casing cutoff at 3000'.
6. Spot 30 sxs. cement plug 1167-1267' over 8 5/8" casing shoe at 1217'.
7. Spot 20 sxs. cement plug surface-50'.
8. Set marker.

THE COMMISSION MUST BE NOTIFIED
24 HOURS PRIOR TO COMMENCING WORK

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Michael R. ... TITLE Area Superintendent DATE 8-17-78

Orig. Signed by

Jerry Stalen

Dist 1, Supv.

AUG 21 1978

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY