

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

3-NMOCC-HOBBS ✓ 1-JL, FOREMAN, JAL
 1-R. J. STARRAK-TULSA 1-FILE
 1-A. B. CARY-MIDLAND 1-BH, FIELD CLERK
 1-ELB, ENGR.

Form C-103
 Supersedes Old
 C-102 and C-103
 Effective 1-1-65

SUNDARY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR INFORMATION TO STATE OR TO OTHERS OR FOR BACK TO A DIFFERENT RESERVOIR. USE APPLICATION FOR PERMIT TO DRILL, C-101, FOR OTHER PROPOSALS.)

1. ☐ OIL WELL ☐ GAS WELL ☐ OTHER- Plugged and abandoned well

2. Name of Operator
Getty Oil Company (George P. Livermore)

3. Address of Operator
P. O. Box 730, Hobbs, New Mexico 88240

4. Location of Well
 UNIT LETTER O 1980 FEET FROM THE East LINE AND 660 FEET FROM
 THE South LINE, SECTION 30 TOWNSHIP 23S RANGE 37E R.M.P.M.

5. Elevation (Show whether DE, RT, GR, etc.)

5a. Indicate Type of Lease
 State ☐ Fee ☒

5. State Oil & Gas Lease No.
-

7. Unit Agreement Issue

8. Farm or Lease Name
Cowden

9. Well No.
2

10. Field and Pool, or Wildcat

12. County
Lea

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK ☐	PLUG AND ABANDON ☐	REMEDIAL WORK ☐	ALTERING CASING ☐
TEMPORARILY ABANDON ☐	CHANGE PLANS ☐	COMMENCE DRILLING OPS. ☐	PLUG AND ABANDONMENT ☐
PULL OR ALTER CASING ☐	OTHER ☐	CASING TEST AND CEMENT JOB ☐	OTHER <u>Re-enter and replug</u> ☒

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1693.

10-27-78 - Rigged up Baber Well Service Unit and Star Tool Co. Rev. Circ. Unit found cement plug in 8 5/8" csg. at 32'; drilled plug to 39' and fell free.

10-28-78 - Lowered 6 3/4" bit and tagged fill in open hole at 1712'. Drilled and cleaned to out to 1716'. Ran 7 7/8" HTC OSC bit and tagged fill in open hole at 1636'.

11-1-78 Drilled and reamed to 1663'.

11-2-78 - Lowered 7 1/2" OD shoe, wash pipe and tools to tag at 1629'; washed to 1663' to Star Tool Co. Rev Circ. Clean out fill and open hole to 1712'.

11-5-78

11-7-78 - Ran 7 7/8" bit and drilled new hole 1712-1730'.

11-8-78 - Installed wellhead; ran 8 5/8" Baker AD-49 B-2 tension pkr., 33 jts. 2 3/8" (1020') 4.7# J-55 tbq.; displaced hole with 75 bbls. sodium bichromate; and set pkr. at 1025' with 8000# tension. Did not plug.

This well to be used as a monitoring well by the NMOCC.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Dale R. Crockett TITLE Area Superintendent DATE December 1, 1978

APPROVED BY _____ TITLE _____ DATE _____

CONDITIONS OF APPROVAL, IF ANY: